






**100R5 Crimp  
Fittings****ORS Swivel Straight****FJ3468-**

**For use with Hose:**  
1503, FC234, FC300, FC350, FC355

**ORS Swivel 45° Elbow****FJ3254-****ORS Swivel 90° Elbow  
(Short)****FJ3255-****SAE 37° (JIC) Swivel****FJ3114-****Straight SAE 45°  
Swivel****FJ3094-**

Complete Fitting Part #	Hose Size	A	D
FJ3468-		mm in	mm in
0404S	-4	54,6 2.15	34,8 1.37
0405S	-5	56,6 2.23	36,6 1.44
0805S	-5	65,5 2.58	45,0 1.77
0606S	-6	59,9 2.36	40,1 1.58
0608S	-8	62,0 2.44	41,9 1.65
0808S	-8	65,8 2.59	45,5 1.79
0810S	-10	68,1 2.68	45,5 1.79
1010S	-10	72,9 2.87	50,5 1.99
1212S	-12	78,0 3.07	55,6 2.19
1616S	-16	85,9 3.38	61,0 2.40
2020S	-20	78,7 3.10	63,2 2.49
2424S	-24	104,4 4.11	66,5 2.62

Complete Fitting Part #	Hose Size	A	D	H
FJ3254-		mm in	mm in	mm in
0404S	-4	46,5 1.83	26,7 1.05	11,2 0.44
0606S	-6	50,6 1.99	30,2 1.19	11,2 0.44
0808S	-8	59,4 2.34	39,1 1.54	15,0 0.59
0810S	-10	62,2 2.45	39,9 1.57	15,0 0.59
1010S	-10	67,3 2.65	45,1 1.77	17,6 0.69
1212S	-12	73,2 2.88	50,8 1.99	21,1 0.83
1616S	-16	82,7 3.25	57,7 2.27	24,1 0.95

Complete Fitting Part #	Hose Size	A	D	H
FJ3255-		mm in	mm in	mm in
0404S	-4	40,9 1.61	21,1 .83	21,4 .84
0605S	-5	46,7 1.84	26,7 1.05	23,1 .91
0406S	-6	43,6 1.72	23,6 .93	21,4 .84
0606S	-6	46,7 1.84	26,7 1.05	23,1 .91
0608S	-8	47,2 1.86	27,1 1.07	23,9 .94
0808S	-8	52,5 2.07	32,3 1.27	29,2 1.15
1010S	-10	58,4 2.30	36,1 1.42	33,3 1.31
1212S	-12	70,6 2.78	48,3 1.90	48,3 1.90
1616S	-16	81,0 3.19	55,9 2.20	56,4 2.22
2020S	-20	92,7 3.65	62,7 2.47	63,4 2.50

Complete Fitting Part #	Hose Size	A	D
FJ3114-		mm in	mm in
0404S	-4	47,8 1.88	27,9 1.10
0604S	-4	51,6 2.03	31,8 1.25
0405S	-5	48,0 1.89	27,9 1.10
0505S	-5	49,3 1.94	29,2 1.15
0606S	-6	51,8 2.04	31,8 1.25
0608S	-8	53,9 2.12	33,5 1.32
0808S	-8	54,6 2.15	34,2 1.35
0810S	-10	58,2 2.29	35,8 1.41
1010S	-10	61,2 2.41	38,9 1.53
1012S	-12	62,0 2.44	39,0 1.54
1212S	-12	61,7 2.43	39,4 1.55
1216S	-16	70,9 2.79	45,7 1.80
1616S	-16	70,4 2.77	43,9 1.73
2020S	-20	75,4 2.97	45,5 1.79
2024S	-24	83,2 3.28	45,5 1.79
2424S	-24	87,1 3.43	49,3 1.94
3232S	-32	108,0 4.25	59,2 2.33

<sup>1</sup>FJ3114-3232S is factory crimp only.

Complete Fitting Part #	Hose Size	A	D
FJ3094-		mm in	mm in
0404S	-4	47,8 1.88	26,9 1.10
0405S	-5	49,3 1.94	27,9 1.15
0505S	-5	53,1 2.09	28,7 1.13
0606S	-6	52,7 2.07	32,5 1.28
0806S	-6	61,2 2.41	33,5 1.32
0808S	-8	54,5 2.15	34,3 1.35
0810S	-10	64,5 2.54	36,8 1.45
1010S	-10	61,2 2.41	38,8 1.53
1212S	-12	61,8 2.43	39,4 1.55


# 100R5 Crimp Fittings

## 45° Elbow

**FJ3243 - Universal Swivel**

**FJ3246 - SAE 45° Swivel**

**FJ3249 - SAE 37° (JIC) Swivel**



### For use with Hose:

1503, FC234, FC300, FC350, FC355


Complete Fitting Part #	Hose Size	A		D		H	
<b>FJ3243-</b>		mm	in	mm	in	mm	in
0404S	-4	43,7	1.72	23,9	.94	8,3	.33
0505S	-5	45,5	1.79	25,1	.99	9,1	.36
0808S	-8	58,4	2.30	40,2	1.58	14,0	.55
0810S	-10	61,5	2.42	39,1	1.54	14,0	.55
1010S	-10	63,5	2.50	41,1	1.62	16,0	.63
<b>FJ3246-</b>							
0606S	-6	49,3	1.94	29,2	1.15	9,9	.39
1212S	-12	71,7	2.82	49,3	1.94	19,7	.77
<b>FJ3249-</b>							
0606S	-6	49,3	1.94	29,2	1.15	9,9	.39
0608S	-8	49,8	1.96	29,2	1.15	9,9	.39
1212S	-12	71,7	2.82	49,3	1.94	19,7	.77
1616S	-16	85,7	3.38	60,7	2.39	27,1	1.07
2020S	-20	100,7	3.96	65,9	2.59	31,0	1.22

## 90° Elbow (Short)

**FJ3244 - Universal Swivel**

**FJ3247 - SAE 45° Swivel**


**FJ3250 - SAE 37° (JIC) Swivel**



Complete Fitting Part #	Hose Size	A		D		H	
<b>FJ3244-</b>		mm	in	mm	in	mm	in
0404S	-4	40,9	1.61	21,1	.83	17,3	.68
0405S	-5	41,2	1.62	21,1	.83	17,3	.68
0505S	-5	42,7	1.68	22,5	.89	19,5	.77
0808S	-8	52,6	2.07	32,3	1.27	27,7	1.09
0810S	-10	55,1	2.17	32,9	1.29	27,7	1.09
1010S	-10	63,7	2.51	41,4	1.63	31,2	1.23
1012S	-12	66,1	2.60	43,4	1.71	31,2	1.23
<b>FJ3247-</b>							
0606S	-6	46,6	1.84	26,7	1.05	21,6	.85
1212S	12	70,6	2.78	48,3	1.90	46,2	1.82
<b>FJ3250-</b>							
0604S	-4	46,5	1.83	26,7	1.05	21,6	.85
0606S	-6	46,7	1.84	26,7	1.05	21,6	.85
0608S	-8	47,0	1.85	26,7	1.05	21,6	.85
1212S	-12	70,6	2.78	48,3	1.90	46,2	1.82
1216S	-16	74,7	2.94	49,5	1.95	46,2	1.82
1616S	-16	80,9	3.19	55,9	2.20	60,8	2.39
2020S	-20	108,5	4.27	73,7	2.90	82,6	3.25
2424S	-24	108,5	4.27	70,8	2.79	77,5	3.05

## Male Pipe

**FJ3152-**



Complete Fitting Part #	Hose Size	A		D	
<b>FJ3152-</b>		mm	in	mm	in
0204S	-4	45,3	1.78	25,5	1.00
0404S	-4	46,9	1.85	27,0	1.06
0405S	-5	47,8	1.88	23,6	.93
0406S	-6	47,1	1.85	27,0	1.06
0606S	-6	47,1	1.85	27,0	1.06
0608S	-8	51,8	2.04	24,9	.98
0808S	-8	54,6	2.15	34,4	1.35
0810S	-10	56,9	2.24	34,5	1.36
1210S	-10	62,7	2.47	35,1	1.38
1212S	-12	56,9	2.24	34,5	1.36
1216S	-16	68,3	2.69	35,6	1.40
1616S	-16	66,3	2.61	41,3	1.63
2020S	-20	75,7	2.98	45,6	1.79
2424S	-24	85,9	3.38	48,2	1.90
3232S	-32	104,3	4.11	55,6	2.19

\*Pictures may not represent actual configuration.

Call Eaton Technical Assistance for details.

#Consult Eaton for most current crimp information.

# Reusable Fittings


## 100R5 Style

### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### Male Pipe


**412-**  
**44-412-**



Dash Size	Thread	Hose Size	A mm in	D mm in	E Ø mm in
412-					
t2-4S*	1/8-27	-04	42,7 1.68	23,4 .92	4,3 .17
t4-4S*	1/4-18	-04	47,2 1.86	28,2 1.11	4,3 .17
t2-5S*	1/8-27	-05	45,2 1.78	25,4 1.00	5,8 .23
t4-5S*	1/4-18	-05	49,8 1.96	30,0 1.18	5,8 .23
t4-6S*	1/4-18	-06	54,1 2.13	31,2 1.23	7,6 .30
t6-6S*	3/8-18	-06	54,1 2.13	31,2 1.23	6,1 .24
t6-8S*	3/8-18	-08	63,0 2.48	33,8 1.33	9,9 .39
8-8S*	1/2-14	-08	69,3 2.73	40,1 1.58	9,1 .36
t8-10S*	1/2-14	-10	73,2 2.88	40,4 1.59	12,2 .48
12-10S*	3/4-14	-10	74,7 2.94	41,9 1.65	12,2 .48
t12-12S*	3/4-14	-12	82,3 3.24	42,4 1.67	15,5 .61
t12-16S	3/4-14	-16	71,1 2.80	38,9 1.53	20,8 .82
t16-16S	1-11½	-16	75,9 2.99	43,7 1.72	20,8 .82
16-20S	1-11½	-20	81,3 3.20	46,7 1.72	24,1 .95
t20-20S	1¼-11½	-20	82,0 3.23	47,5 1.87	26,7 1.05
20-24S	1¼-11½	-24	90,9 3.58	53,8 2.12	32,5 1.28
t24-24S	1½-11½	-24	88,4 3.48	51,6 2.03	32,5 1.28
t32-32S	2-11½	-32	102,9 4.05	55,9 2.20	44,5 1.75
<b>44-412-</b>					
40-40	2½-8	-40	127,8 5.03	79,5 3.13	53,8 2.12
48-48	3-8	-48	129,3 5.09	81,0 3.19	68,3 2.69

### Male Pipe

**4412-**




4412-	Thread	Hose Size	mm in	mm in	mm in
2-4S	1/8-27	-04	42,7 1.68	23,6 .93	3,3 .13
4-4S	1/4-18	-04	47,5 1.87	28,4 1.12	3,3 .13
4-5S	1/4-18	-05	49,8 1.96	30,0 1.18	4,3 .17
4-6S†	1/4-18	-06	54,1 2.13	31,2 1.23	6,1 .24
6-6S	3/8-18	-06	54,1 2.13	31,2 1.23	5,8 .23
4-8S	1/4-18	-08	63,0 2.48	33,8 1.33	7,6 .30
6-8S	3/8-18	-08	63,0 2.48	33,8 1.33	9,1 .36
8-8S	1/2-14	-08	69,3 2.73	40,1 1.58	9,1 .36
8-10S	1/2-14	-10	73,2 2.88	40,4 1.59	11,7 .46
12-10S	3/4-14	-10	74,7 2.94	41,9 1.65	11,7 .46
8-12S	1/2-14	-12	82,3 3.24	42,7 1.68	12,4 .49
12-12S	3/4-14	-12	82,3 3.24	42,4 1.67	14,0 .55

### SAE 37° (JIC) swivel

**411-**

**44-411-**



411-	Thread	Hose Size	mm in	mm in	mm in
t4S*	7/16-20	-4	44,5 1.75	25,4 1.00	4,3 .17
t5S*	1/2-20	-5	48,3 1.90	28,4 1.12	5,8 .23
t6S*	9/16-18	-6	52,1 2.05	29,2 1.15	7,6 .30
t8S*	3/4-16	-8	64,0 2.52	35,1 1.38	9,9 .39
10S*	7/8-14	-10	71,1 2.80	38,4 1.51	12,2 .48
t12S*	1 1/16-12	-12	80,0 3.15	40,1 1.58	15,5 .61
t16S*	1 5/16-12	-16	71,6 2.82	39,4 1.55	20,8 .82
t20S*†††	1 5/8-12	-20	76,2 3.00	41,7 1.64	26,7 1.05
t24S*†††	1 7/8-12	-24	83,3 3.28	46,5 1.83	32,5 1.28
t32S*†††	2 1/2-12	-32	98,6 3.88	51,6 2.03	44,5 1.75
<b>44-411-</b>					
40*	3-12	-40	105,7 4.16	57,2 2.25	55,9 2.20
48*	3 1/2-12	-48	108,7 4.28	60,5 2.38	71,1 2.80

\*Requires tools for assembly.

†Also supplied in brass. To order, substitute "B" for "S" in part number.

††Available in stainless steel. To order, drop the "S" suffix and add "259—" prefix.

NOTE: For correct socket part number, see page 65

# Reusable Fittings


## 100R5 Style

### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### SAE 37° (JIC) swivel


4411-



Dash Size	Thread	Hose Size	A mm in	D mm in	E Ø mm in
4411-					
4S****	7/16-20	-04	50,0 1.97	31,2 1.23	3,3 .13
4-5S	7/16-20	-05	52,8 2.08	33,0 1.30	4,3 .17
5S****	1/2-20	-05	53,8 2.12	34,3 1.35	4,6 .18
6S****	9/16-18	-06	59,2 2.33	36,3 1.43	6,1 .24
8-6S	3/4-16	-06	61,5 2.42	38,6 1.52	6,1 .24
6-8S	9/16-18	-08	68,1 2.68	38,9 1.53	7,6 .30
8S****	3/4-16	-08	70,6 2.78	41,1 1.62	9,1 .36
10-8S	7/8-14	-08	74,9 2.95	45,7 1.80	9,1 .36
8-10S	3/4-16	-10	74,2 2.92	41,7 1.64	9,9 .39
10S****	7/8-14	-10	78,7 3.10	46,0 1.81	11,7 .46
12-10S	1 1/16-12	-10	81,0 3.19	48,5 1.91	11,7 .46
10-12S	7/8-14	-12	86,4 3.40	46,5 1.83	14,0 .55
12S****	1 1/16-12	-12	88,6 3.49	48,8 1.92	14,0 .55
14-12S	1 3/16-12	-12	90,6 3.56	50,5 1.99	14,0 .55
16S****	1 5/16-12	-16	81,0 3.19	49,0 1.93	20,8 .82
20S	1 5/8-12	-20	87,1 3.43	52,6 2.07	26,7 1.05
20-24S	1 5/8-12	-24	92,7 3.65	55,6 2.19	26,9 1.06
24S	1 7/8-12	-24	93,5 3.68	56,4 2.22	32,5 1.28
32S	2 1/2-12	-32	111,5 4.39	64,8 2.55	44,5 1.75

### SAE 45° swivel


401-



Dash Size	Thread	Hose Size	A mm in	D mm in	E Ø mm in
401-					
4S*†	7/16-20	-04	44,5 1.75	25,4 1.00	4,3 .17
5S*†	1/2-20	-05	48,3 1.90	28,4 1.12	5,8 .23
6S*†	5/8-18	-06	52,1 2.05	29,2 1.15	7,6 .30
8S*†	3/4-16	-08	64,0 2.52	35,1 1.38	9,9 .39
10S*†	7/8-14	-10	71,1 2.80	38,4 1.51	12,2 .48
12S*†	11/16-14	-12	76,7 3.02	36,8 1.45	15,5 .61

### SAE 45° swivel


4401-



Dash Size	Thread	Hose Size	A mm in	D mm in	E Ø mm in
4401-					
4S	7/16-20	-04	50,0 1.97	31,0 1.22	3,3 .13
5S	1/2-20	-05	53,8 2.12	34,0 1.34	4,3 .17
6S	5/8-18	-06	59,9 2.36	37,1 1.46	6,1 .24
8S	3/4-16	-08	70,6 2.78	41,1 1.62	9,1 .36
10S	7/8-14	-10	78,7 3.10	46,0 1.81	11,7 .46
12S	1 1/16-14	-12	88,6 3.49	48,8 1.92	14,0 .55

### SAE PTT swivel

406-



Dash Size	Thread	Hose Size	A mm in	D mm in	E Ø mm in
406-					
16B*****	1 5/16-14	-16	66,0 2.60	33,8 1.33	20,8 .82
20B*****	1 5/8-14	-20	72,6 2.86	38,1 1.50	26,7 1.05

\*Requires tools for assembly.


† Also supplied in brass. To order, substitute "B" for "S" in part number.

\*\*\*\* Available in stainless steel. To order, drop the "S" suffix and add "259—" prefix.


\*\*\*\*\* Also supplied in steel. To order, drop "B" suffix and substitute "S" in part number.

NOTE: For correct socket part number, see page 65.


## Reusable Fittings

**100R5 Style****SAE Male O-Ring Boss\*\*****190463-****For use with Hose:**302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355


Dash Size	Thread	Hose Size	A	D	EØ
			mm in	mm in	mm in
190463-					
6S	9/16-18	-06	49,5 1.95	26,7 1.05	6,1 .24
8S	3/4-16	-08	59,7 2.35	30,5 1.20	9,1 .36
10S	7/8-14	-10	66,8 2.63	34,0 1.34	9,1 .36

**SAE 37° (JIC) Male Flare****4414-**

Dash Size	Thread	Hose Size	A	D	EØ
			mm in	mm in	mm in
4414-					
4S	7/16-20	-04	47,0 1.85	27,9 1.10	3,3 .13
5S	1/2-20	-05	49,5 1.95	29,7 1.17	4,3 .17
6S	9/16-18	-06	53,8 2.12	31,0 1.22	6,1 .24
8S	3/4-16	-08	65,3 2.57	36,1 1.42	9,1 .36
10S	7/8-14	-10	73,2 2.88	40,6 1.60	11,7 .46
12-10S	1 1/16-12	-10	77,5 3.05	44,7 1.76	11,7 .46
12S	1 1/16-12	-12	85,1 3.35	45,2 1.78	14,0 .55
16-12S	1 5/16-12	-12	86,4 3.40	46,5 1.83	14,0 .55
16S	1 5/16-12	-16	75,2 2.96	42,9 1.69	20,8 .82
20S	1 5/8-12	-20	81,8 3.22	47,2 1.86	26,7 1.05
24S	1 7/8-12	-24	87,4 3.44	50,5 1.99	32,5 1.28
32S	2 1/2-12	-32	107,2 4.22	60,5 2.38	44,5 1.75

**SAE 45° Male Flare****4402-**

Dash Size	Thread	Hose Size	A	D	EØ
			mm in	mm in	mm in
4402-					
4S	7/16-20	-04	45,7 1.80	26,9 1.06	3,3 .13
4-5S	7/16-20	-05	48,3 1.90	28,4 1.12	4,3 .17
5S	1/2-20	-05	50,0 1.97	30,0 1.18	4,3 .17
6S	5/8-18	-06	55,6 2.19	32,5 1.28	6,1 .24
8S	3/4-16	-08	67,6 2.66	38,6 1.52	9,1 .36
10S	7/8-14	-10	76,2 3.00	43,7 1.72	11,7 .46
12-10S	1 1/16-14	-10	81,3 3.20	48,3 1.90	11,7 .46
12S	1 1/16-14	-12	88,9 3.50	48,8 1.92	14,2 .56

**Lifesaver†****190000-**

Dash Size	Tube	Hose Size	A	B†	D	EØ
			mm in	mm in	mm in	mm in
190000-						
4S	1/4	-04	34,5 1.36	6,4 .25	15,7 .62	3,3 .13
5S	5/16	-05	38,9 1.53	7,9 .31	19,1 .75	4,6 .18
5-6S	5/16	-06	41,4 1.63	7,9 .31	18,5 .73	6,1 .24
6S	3/8	-06	41,4 1.63	9,7 .38	18,5 .73	6,1 .24
6-8S	3/8	-08	51,8 2.04	9,7 .38	22,6 .89	7,1 .28
8S	1/2	-08	51,8 2.04	12,7 .50	22,6 .89	9,1 .36
10S	5/8	-10	55,6 2.19	15,7 .62	22,9 .90	11,7 .46
8-12S	1/2	-12	63,2 2.49	12,7 .50	23,4 .92	9,9 .39
12S	3/4	-12	63,2 2.49	19,1 .75	23,4 .92	14,0 .55
16S	1	-16	52,1 2.05	25,4 1.00	19,8 .78	20,8 .82
16-20S	1	-20	57,4 2.26	25,4 1.00	22,9 .90	20,8 .82
18-20S	1 1/8	-20	57,4 2.26	28,4 1.12	22,9 .90	23,9 .94
20S	1 1/4	-20	57,4 2.26	31,8 1.25	22,9 .90	26,7 1.05
24-20S	1/2	-20	59,2 2.33	38,1 1.50	24,4 .96	26,7 1.05
16-24S	1	-24	61,5 2.42	25,4 1.00	24,6 .97	20,8 .82
20-24S	1 1/4	-24	59,9 2.36	31,8 1.25	22,9 .90	26,7 1.05
24-24S	1/2	-24	61,5 2.42	38,1 1.50	24,6 .97	32,5 1.28
20-32S	1 1/4	-32	73,4 2.89	31,8 1.25	26,7 1.05	26,9 1.06
24-32S	1/2	-32	71,9 2.83	38,1 1.50	24,9 .98	34,8 1.37
32-32S	2	-32	73,4 2.89	50,8 2.00	26,7 1.05	44,5 1.75
40S	2 1/2	-40	82,8 3.26	63,5 2.50	34,5 1.36	56,1 2.21

\*\*See pages 194, 195 for o-rings.

† "B" dimension is counterbore diameter for mating tubing.

NOTE: For correct socket part number, see page 65.

# Reusable Fittings

## 100R5 Style

### For use with Hose:


302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### 45° Elbow

### 190297 - Universal Swivel

### 190299 - SAE 45° Swivel

### 190265 - SAE 37° (JIC) Swivel




Dash Size	Thread	Hose Size	A	D	EØ	H
<b>190297-</b>						
4S	7/16-20	-04	47,0 1.85	27,9 1.10	3,3 .13	8,4 .33
4-5S	7/16-20	-05	51,1 2.01	31,2 1.23	3,8 .15	8,4 .33
5S	1/2-20	-05	52,6 2.07	32,8 1.29	4,6 .18	9,1 .36
8-6S	3/4-16	-06	67,1 2.64	44,2 1.74	6,1 .24	14,0 .55
8S	3/4-16	-08	75,9 2.99	46,7 1.72	9,1 .36	14,0 .55
8-10S	3/4-16	-10	79,8 3.14	47,0 1.85	9,9 .39	14,0 .55
10S	7/8-14	-10	82,3 3.24	49,5 1.95	11,7 .46	16,3 .64
10-12S	7/8-14	-12	89,9 3.54	50,0 1.97	12,2 .48	16,3 .64
<b>190299-</b>						
6S	5/8-18	-06	56,6 2.23	33,8 1.33	6,1 .24	9,9 .39
12S	1 1/16-14	-12	96,0 3.78	56,1 2.21	14,0 .55	19,8 .78
<b>190265-</b>						
6-5S	9/16-18	-05	54,1 2.13	34,3 1.35	4,3 .17	9,9 .39
6S	9/16-18	-06	56,6 2.23	33,8 1.33	6,1 .24	9,9 .39
12S	1 1/16-12	-12	96,0 3.78	56,1 2.21	14,0 .55	19,8 .78
16-12S	1 5/16-12	-12	101,6 4.00	61,7 2.43	14,0 .55	25,1 .99
16S	1 5/16-12	-16	95,0 3.74	62,7 2.47	20,8 .82	27,2 1.07
20S	1 1/8-12	-20	106,9 4.21	72,4 2.85	26,7 1.05	31,0 1.22

### 90° Elbow (Short)

### 190296 - Universal Swivel,

### 190302 - SAE 45° Swivel,

### 190261 - SAE 37° (JIC) Swivel



NOTE: For correct socket part number, see page 65.


Dash Size	Thread	Hose Size	A	D	EØ	H
<b>190296-</b>						
4S	7/16-20	-04	44,2 1.74	25,1 .99	3,3 .13	17,3 .68
5S	1/2-20	-05	49,8 1.96	30,0 1.18	4,3 .17	19,6 .77
8S	3/4-16	-08	70,1 2.76	40,9 1.61	9,1 .36	27,7 1.09
10S	7/8-14	-10	74,7 2.94	41,9 1.65	11,7 .46	31,2 1.23
8-12S	3/4-16	-12	81,5 3.21	41,7 1.64	9,9 .39	27,7 1.09
<b>190302-</b>						
6S	5/8-18	-06	54,1 2.13	31,2 1.23	6,1 .24	21,6 .85
12S	1 1/16-14	-12	95,0 3.74	55,1 2.17	14,0 .55	46,2 1.82
<b>190261-</b>						
6S	9/16-18	-06	54,1 2.13	31,2 1.23	6,1 .24	21,6 .85
12S	1 1/16-12	-12	95,0 3.74	55,1 2.17	14,0 .55	46,2 1.82
16-12S	1 5/16-12	-12	95,0 3.74	55,1 2.17	14,0 .55	54,4 2.14
16S	1 5/16-12	-16	90,2 3.55	57,9 2.28	20,8 .82	58,4 2.30
20-16S	1 5/8-12	-16	90,2 3.55	57,9 2.28	19,3 .76	63,5 2.50
20S	1 5/8-12	-20	102,1 4.02	67,3 2.65	26,7 1.05	69,9 2.75
20-24S	1 5/8-12	-24	104,4 4.11	67,6 2.66	26,7 1.05	69,9 2.75

### 90° Elbow (Long)

### 190295 - Universal Swivel,

### 190301 - SAE 45° Swivel,

### 190260 - SAE 37° (JIC) Swivel



Dash Size	Thread	Hose Size	A	D	EØ	H
<b>190295-</b>						
4S	7/16-20	-04	44,2 1.74	25,1 .99	3,3 .13	45,7 1.80
5S	1/2-20	-05	49,8 1.96	30,0 1.18	4,6 .18	45,0 1.77
8S	3/4-16	-08	73,2 2.88	43,9 1.73	9,1 .36	61,7 2.43
10S	7/8-14	-10	81,0 3.19	48,3 1.90	11,7 .46	65,3 2.57
10-12S	7/8-14	-12	88,6 3.49	48,8 1.92	12,2 .48	65,3 2.57
<b>190301-</b>						
6S	5/8-18	-06	54,1 2.13	31,2 1.23	6,1 .24	55,4 2.18
12S	1 1/16-14	-12	95,0 3.74	55,1 2.17	14,0 .55	94,7 3.73
<b>190260-</b>						
6S	9/16-18	-06	54,1 2.13	31,2 1.23	6,1 .24	55,4 2.18
12S	1 1/16-12	-12	95,0 3.74	55,1 2.17	14,0 .55	94,7 3.73
16S	1 5/16-12	-16	90,2 3.55	57,9 2.28	20,8 .82	116,3 4.58
20S	1 5/8-12	-20	102,1 4.02	67,3 2.65	26,7 1.05	140,5 5.53

# Reusable Fittings


## 100R5 Style

For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### Code 61 SAE J518 Straight Split Flange


4775-



Dash Size	Flange Head Dia.	Hose Size	A	D	EØ
	mm in		mm in	mm in	mm in
4775-					
8S	30,2 1.19	-08	70,4 2.77	41,1 1.62	9,1 .36
8-10S	30,2 1.19	-10	84,3 3.32	51,6 2.03	11,7 .46
16-10S	44,5 1.75	-10	75,4 2.97	42,7 1.68	11,7 .46
12S	38,1 1.50	-12	80,3 3.16	40,4 1.59	14,0 .55
16-12S	44,5 1.75	-12	90,2 3.55	50,3 1.98	14,0 .55
20-12S	50,8 2.00	-12	90,2 3.55	50,3 1.98	14,0 .55
16S	44,5 1.75	-16	70,4 2.77	38,1 1.50	20,8 .82
20-16S	50,8 2.00	-16	85,3 3.36	53,1 2.09	20,8 .82
24-16S	60,5 2.38	-16	86,9 3.42	54,4 2.14	20,8 .82
16-20S	44,5 1.75	-20	75,9 2.99	41,1 1.62	20,8 .82
20S	50,8 2.00	-20	90,9 3.58	56,1 2.21	26,7 1.05
32-20S	71,4 2.81	-20	92,5 3.64	57,9 2.28	26,7 1.05
16-24S	44,5 1.75	-24	94,7 3.73	57,9 2.28	20,8 .82
20-24S	50,8 2.00	-24	93,2 3.67	56,4 2.22	26,7 1.05
24S	60,5 2.38	-24	102,1 4.02	65,0 2.56	32,5 1.28
32-24S	71,4 2.81	-24	102,1 4.02	65,0 2.56	32,5 1.28
20-32S	50,8 2.00	-32	133,6 5.26	86,9 3.42	26,9 1.06
24-32S	60,5 2.38	-32	112,3 4.42	65,5 2.58	34,8 1.37
32S	71,4 2.81	-32	125,0 4.92	78,2 3.08	44,5 1.75
40-32S	84,1 3.31	-32	126,5 4.98	79,8 3.14	44,5 1.75
40*	84,1 3.31	-40	136,1 5.36	87,6 3.45	56,1 2.21

### Code 61 SAE J518 22½° Split Flange


4776-



Dash Size	Flange Head Dia.	Hose Size	A	D	EØ	H
	mm in		mm in	mm in	mm in	mm in
4776-						
16S	44,5 1.75	-16	90,2 3.55	57,9 2.28	20,8 .82	12,7 .50
32-16S	71,4 2.81	-16	89,4 3.52	57,4 2.26	20,8 .82	12,4 .49
20S	50,8 2.00	-20	97,0 3.82	62,2 2.45	26,7 1.05	12,7 .50
32-20S	71,4 2.81	-20S	98,6 3.88	63,8 2.51	26,7 1.05	13,2 .52
32S	71,4 2.81	-32	116,6 4.59	69,9 2.75	44,5 1.75	12,7 .50

### Code 61 SAE J518 30° Split Flange

198046-



Dash Size	Flange Head Dia.	Hose Size	A	D	EØ	H
	mm in		mm in	mm in	mm in	mm in
190846-						
16-12S	44,5 1.75	-12	91,4 3.60	51,6 2.03	14,0 .55	11,4 .45
16S	44,5 1.75	-16	84,3 3.32	52,1 2.05	20,8 .82	12,7 .50
20-16S	50,8 2.00	-16	84,3 3.32	52,1 2.05	20,8 .82	12,7 .50
20S	50,8 2.00	-20	92,2 3.63	57,4 2.26	26,7 1.05	13,2 .52
24S	60,5 2.38	-24	100,6 3.96	63,8 2.51	32,5 1.28	14,7 .58
32S	71,4 2.81	-32	118,9 4.68	72,1 2.84	44,5 1.75	16,5 .65

\* Order as 39-4775-40.

NOTE: For flanges, split flange halves, kits and o-rings see pages 190-194.

NOTE: For correct socket part number, see page 65.

# Reusable Fittings


## 100R5 Style

### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### Code 61 SAE J518 45° Split Flange


**4777-**



Dash Size	Flange Head Dia.	Hose Size	A	D	EØ	H
4777-	mm in		mm in	mm in	mm in	mm in
8S	30,2 1.19	-08	87,4 3.44	58,4 2.30	9,1 .36	25,4 1.00
12S	38,1 1.50	-12	102,1 4.02	62,2 2.45	14,0 .55	25,4 1.00
16-12S	44,5 1.75	-12	102,1 4.02	62,2 2.45	14,0 .55	25,4 1.00
20-12S	50,8 2.00	-12	102,1 4.02	62,2 2.45	14,0 .55	25,4 1.00
16S	44,5 1.75	-16	96,5 3.80	64,3 2.53	20,8 .82	28,4 1.12
16-20S	44,5 1.75	-20	101,9 4.01	67,3 2.65	20,8 .82	28,4 1.12
20-16S	50,8 2.00	-16	96,5 3.80	64,3 2.53	20,8 .82	28,4 1.12
20S	50,8 2.00	-20	104,6 4.12	69,9 2.75	26,7 1.05	28,4 1.12
24-20S	60,5 2.38	-20	104,6 4.12	69,9 2.75	26,7 1.05	28,4 1.12
32-20S	46,0 1.81	-20	105,7 4.16	71,1 2.80	26,7 1.05	29,7 1.17
24S	60,5 2.38	-24	111,3 4.38	74,2 2.92	32,5 1.28	28,4 1.12
24-32S	60,5 2.38	-32	121,4 4.78	74,7 2.94	34,8 1.37	28,4 1.12
32-24S	71,4 2.81	-24	111,3 4.38	74,2 2.92	32,5 1.28	28,4 1.12
32S	71,4 2.81	-32	131,6 5.18	84,6 3.33	44,5 1.75	31,8 1.25
40-32S	84,1 3.31	-32	132,6 5.22	85,9 3.38	44,5 1.75	33,0 1.30
40*	84,1 3.31	-40	167,1 6.58	118,6 4.67	56,1 2.21	42,1 1.66

### Code 61 SAE J518 60° Split Flange


**191395-**



Dash Size	Flange Head Dia.	Hose Size	A	D	EØ	H
191395-	mm in		mm in	mm in	mm in	mm in
12S	38,1 1.50	-12	105,4 4.15	65,5 2.58	14,0 .55	41,1 1.62
16S	44,5 1.75	-16	98,0 3.86	66,0 2.60	20,8 .82	41,7 1.64
20S	50,8 2.00	-20	107,2 4.22	72,6 2.86	26,7 1.05	41,7 1.64
24S	60,5 2.38	-24	120,1 4.73	83,3 3.28	32,5 1.28	50,8 2.00

### Code 61 SAE J518 90° Split Flange

**4779-**



Dash Size	Flange Head Dia.	Hose Size	A	D	EØ	H
4779-	mm in		mm in	mm in	mm in	mm in
8S	30,2 1.19	-08	73,2 2.88	43,9 1.73	9,1 .36	41,1 1.62
12S	38,1 1.50	-12	95,0 3.74	55,1 2.17	14,0 .55	53,8 2.12
16-12S	44,5 1.75	-12	95,0 3.74	55,1 2.17	14,0 .55	53,8 2.12
12-16S	38,1 1.50	-16	83,8 3.30	51,6 2.03	20,8 .82	53,8 2.12
16S	44,5 1.75	-16	90,2 3.55	57,9 2.28	20,8 .82	60,5 2.38
20-16S	50,8 2.00	-16	90,2 3.55	57,9 2.28	20,8 .82	60,5 2.38
16-20S	44,5 1.75	-20	95,5 3.76	60,9 2.40	20,8 .82	60,5 2.38
20S	50,8 2.00	-20	102,1 4.02	67,3 2.65	26,7 1.05	63,5 2.50
24-20S	60,5 2.38	-20	102,1 4.02	67,3 2.65	26,7 1.05	63,5 2.50
32-20S	71,4 2.81	-20	102,1 4.02	67,3 2.65	26,7 1.05	65,0 2.56
20-24S	50,8 2.00	-24	104,4 4.11	67,6 2.66	26,7 1.05	63,5 2.50
24S	60,5 2.38	-24	112,2 4.42	75,4 2.97	32,5 1.28	69,9 2.75
24-32S	60,5 2.38	-32	122,7 4.83	75,7 2.98	34,8 1.37	69,9 2.75
32S	71,4 2.81	-32	136,9 5.39	90,2 3.55	44,5 1.75	82,6 3.25
40-32S	84,1 3.31	-32	136,9 5.39	90,2 3.55	44,5 1.75	84,1 3.31
40**	84,1 3.31	-40	184,4 7.26	136,1 5.36	56,1 2.21	131,8 5.19

NOTE: For flanges, split flange halves, kits and o-rings see pages 190-194. \*Order as 39-4775-40

NOTE: For correct socket part number, see page 65. \*\*Order as 39-4779-40

# Reusable Fittings


## 100R5 Style

### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### Male Inverted Flare


**190277-**



Dash Size	Thread	Hose Size	A	D	EØ
<b>190277-</b>			mm in	mm in	mm in
4S	7/16-20	-04	45,7 1.80	26,7 1.05	3,3 .13

### Male/Female Inverted Flare


**190276-**



Dash Size	Thread	Hose Size	A	D	EØ
<b>190276-</b>			mm in	mm in	mm in
4S	5/8-18(M)	-04	52,1 2.05	33,0 1.30	3,3 .13
	7/16-24(F)				

### Female Inverted Flare


**403-**



Dash Size	Thread	Hose Size	A	D	EØ
<b>403-</b>			mm in	mm in	mm in
5S	1/2-20	-05	41,1 1.62	21,3 .84	5,8 .23
6S	5/8-18	-06	45,2 1.78	22,4 .88	7,6 .30

### Compression Ball Sleeve


**FC7031-**



Dash Size	Thread	Hose Size	A	D	EØ
<b>FC7031-</b>			mm in	mm in	mm in
0808-206	1/2	-08	59,9 2.36	30,5 1.20	9,1 .36
1010-206	5/8	-10	66,5 2.62	34,0 1.34	11,7 .46

### Straight SAE Male Inverted Flare

**190111-**



Dash Size	Thread	Hose Size	A	D	EØ
<b>190111-</b>			mm in	mm in	mm in
4S	7/16-24	-04	62,5 2.46	43,4 1.71	3,3 .13
5S	1/2-20	-05	66,5 2.62	46,7 1.84	4,6 .18
5-6S	1/2-20	-06	69,1 2.72	46,2 1.82	6,1 .24
6S	5/8-18	-06	69,1 2.72	46,2 1.82	6,1 .24
6-8S	5/8-18	-08	79,5 3.13	50,8 1.98	7,1 .28
8S	3/4-18	-08	81,3 3.20	52,1 2.05	9,1 .36

NOTE: For correct socket part number, see page 65.

# Reusable Fittings


## 100R5 Style

### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### 15° Elbow SAE Male Inverted Flare

**190350-**




Dash Size	Thread	Hose Size	A mm in	D mm in	EØ mm in	H mm in
190350-						

6S      5/8-18      -06      82,8 3.26      59,9 2.36      6,1 .24      9,4 .37

### 45° Elbow SAE Male Inverted Flare


**190371-**



Dash Size	Thread	Hose Size	A mm in	D mm in	EØ mm in	H mm in
190371-						
4S	7/16-20	-04	69,6 2.74	50,5 1.99	3,3 .13	24,4 .96
5S	1/2-20	-05	73,7 2.90	53,8 2.12	4,3 .17	24,4 .96
6S	5/8-18	-06	76,2 3.00	53,3 2.10	6,1 .24	24,4 .96
8S	3/4-18	-08	86,1 3.39	56,9 2.24	9,1 .36	23,6 .93
10S	5/8-18	-10	95,0 3.74	62,0 2.44	11,7 .46	26,2 1.03

### 90° Elbow (Short) SAE Male Inverted Flare


**190235-**



Dash Size	Thread	Hose Size	A mm in	D mm in	EØ mm in	H mm in
190235-						
4S	7/16-24	-04	59,9 2.36	41,1 1.62	3,3 .13	42,9 1.69
7-4S	11/16-18	-04	53,8 2.12	34,5 1.36	3,3 .13	46,7 1.84
8-4S	3/4-18	-04	53,8 2.12	34,5 1.36	3,3 .13	46,7 1.84
5S	1/2-20	-05	64,3 2.53	44,5 1.75	4,6 .18	42,9 1.69
6S	5/8-18	-06	66,8 2.63	43,9 1.73	6,1 .24	43,9 1.73
7-6S	11/16-18	-06	66,8 2.63	43,9 1.73	6,1 .24	43,9 1.73
6-8S	5/8-18	-08	77,2 3.04	48,0 1.89	7,1 .28	43,9 1.73
7-8S	11/16-18	-08	77,2 3.04	48,0 1.89	7,1 .28	43,9 1.73
8S	3/4-18	-08	77,2 3.04	48,0 1.89	9,1 .36	44,5 1.75
10S	7/8-18	-10	87,4 3.44	54,6 2.15	11,7 .46	56,4 2.22
8-12S	3/4-18	-12	88,6 3.49	48,8 1.92	9,9 .39	44,5 1.75

### 90° Elbow (Long) SAE Male Inverted Flare

**190325-**



Dash Size	Thread	Hose Size	A mm in	D mm in	EØ mm in	H mm in
190325-						

6S      5/8-18      -06      93,2 3.67      70,4 2.77      6,1 .24      69,3 2.73

NOTE: For correct socket part number, see page 65.

# Reusable Fittings

## 100R5 Style

SPECIALTY &  
TRUCK HOSE

LOW & MEDIUM  
PRESSURE HOSE

HIGH PRESSURE HOSE

HOSE FITTINGS

ADAPTERS &  
TUBE FITTINGS

ACCESSORIES &  
ASSEMBLY INSTRUCTIONS

HOSE ASSEMBLY  
EQUIPMENT


APPENDICES

### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

#### ORS Swivel Straight


**FJ9706-**



Dash Size	"T" Thread	Hose Size	A mm in	D mm in	EØ mm in
<b>FJ9706-</b>					
0404S	9/16-18	-04	53,1 2.09	34,0 1.34	3,3 .13
0405S	9/16-18	-05	51,6 2.03	31,8 1.25	4,3 .17
0606S	11/16-16	-06	61,7 2.43	38,9 1.53	6,1 .24
0808S	13/16-16	-08	79,5 3.13	50,8 1.98	9,1 .36
1010S	1-14	-10	85,6 3.37	52,8 2.08	11,7 .46
1212S	1 3/16-12	-12	93,5 3.68	53,6 2.11	14,0 .55
1616S	1 7/16-12	-16	88,9 3.50	56,6 2.23	20,8 .82
2020S	1 11/16-12	-20	92,5 3.64	57,9 2.28	26,7 1.05
2424S	2-12	-24	98,0 3.86	60,9 2.40	32,0 1.26

#### ORS Swivel 45° Elbow


**FJ9707-**



Dash Size	"T" Thread	Hose Size	A mm in	D mm in	EØ mm in	H mm in
<b>FJ9707-</b>						
0404S	9/16-18	-04	49,8 1.96	30,7 1.21	3,3 .13	10,4 .41
0606S	11/16-16	-06	57,7 2.27	34,8 1.37	5,6 .22	10,9 .43
0808S	13/16-16	-08	68,1 2.68	45,2 1.78	6,1 .24	15,0 .59
1010S	1-14	-10	77,0 3.03	47,8 1.88	9,1 .36	15,0 .59
1212S	1 3/16-12	-12	85,9 3.38	52,8 2.08	11,7 .46	16,5 .65
1616S	1 7/16-12	-16	97,5 3.84	57,7 2.27	14,0 .55	21,1 .83
2020S	1 11/16-12	-20	91,9 3.62	59,7 2.35	19,3 .76	23,9 .94
2424S	2-12	-24	103,9 4.09	69,1 2.72	25,7 1.01	25,4 1.00

#### ORS Swivel 90° Elbow (Short drop)


**FJ9708-**



Dash Size	"T" Thread	Hose Size	A mm in	D mm in	EØ mm in	H mm in
<b>FJ9708-</b>						
0404S	9/16-18	-04	45,7 1.80	26,7 1.05	3,3 .13	20,8 .82
0606S	11/16-16	-06	54,1 2.13	31,2 1.23	5,6 .22	22,9 .90
0808S	13/16-16	-08	70,1 2.76	40,9 1.61	9,1 .36	29,2 1.15
1010S	1-14	-10	77,0 3.03	44,2 1.74	11,7 .46	32,3 1.27
1212S	1 3/16-12	-12	95,0 3.74	55,1 2.17	14,0 .55	47,8 1.88
1616S	7/16-12	-16	90,2 3.55	57,9 2.28	19,3 .76	56,1 2.21
2020S	1 11/16-12	-20	102,1 4.02	67,3 2.65	25,7 1.01	63,8 2.51
2424S	2-12	-24	112,2 4.42	75,4 2.97	32,0 1.26	68,6 2.70

#### ORS Swivel 90° Elbow (Long drop)

**FJ9709-**



Dash Size	"T" Thread	Hose Size	A mm in	D mm in	EØ mm in	H mm in
<b>FJ9709-</b>						
0404S	9/16-18	-04	45,7 1.80	26,7 1.05	3,3 .13	45,7 1.80
0606S	11/16-16	-06	57,2 2.25	34,3 1.35	5,6 .22	54,1 2.13
0808S	13/16-16	-08	73,2 2.88	43,9 1.73	9,1 .36	63,8 2.51
1010S	1-14	-10	77,0 3.03	44,2 1.74	11,7 .46	70,1 2.76
1212S	1 3/16-12	-12	95,0 3.74	55,1 2.17	14,0 .55	96,0 3.78
1616S	7/16-12	-16	90,2 3.55	57,7 2.27	19,3 .76	114,3 4.50
2020S	1 11/16-12	-20	102,1 4.02	67,3 2.65	25,7 1.01	129,3 5.09
2424S	2-12	-24	112,2 4.42	75,4 2.97	32,0 1.26	140,7 5.54

NOTE: For correct socket part number, see page 65.

# Reusable Fittings


## 100R5 Style

### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### BSP Male


**07.340-**



Dash Size	"T" Thread	Hose Size	A mm in	D mm in	E Ø mm in
<b>07.340-</b>					
4-4	1/4-19	-04	46,5 1.83	27,5 1.08	3,2 .13
6-6	3/8-19	-06	53,0 2.09	30,0 1.18	6,0 .24
8-8	1/2-14	-08	64,0 2.52	34,5 1.35	9,0 .35
10-10	5/8-14	-10	71,0 2.80	38,0 1.50	11,5 .45
12-12	3/4-14	-12	79,5 3.13	39,5 1.56	14,0 .55
16-16	1-11	-16	71,5 2.81	39,0 1.54	21,0 .83
20-20	1 1/4-11	-20	74,0 2.91	39,5 1.56	26,5 1.04
24-24	1 1/2-11	-24	77,5 3.05	40,5 1.59	32,5 1.28
32-32	2-11	-32	95,5 3.76	48,5 1.91	44,5 1.75

### BSP Female Swivel

**07.421-**



Dash Size	Thread	Hose Size	A mm in	D mm in	E Ø mm in
<b>07.421-</b>					
4-4	1/4-19	-04	52,0 2.05	33,0 1.30	3,0 .13
6-6	3/8-19	-06	59,5 2.34	36,5 1.44	6,0 .24
8-6	1/2-19	-06	61,0 2.40	38,0 1.50	6,0 .24
8-8	1/2-14	-08	70,0 2.76	40,5 1.59	9,0 .35
10-10	5/8-14	-10	75,5 2.97	43,0 1.69	11,5 .45
12-10	3/4-14	-10	77,0 3.03	44,0 1.73	11,5 .45
12-12	3/4-14	-12	84,5 3.33	44,5 1.75	14,0 .55
16-16	1-11	-16	78,0 3.07	45,5 1.79	21,0 .83
20-20	1 1/4-11	-20	81,5 3.21	47,0 1.85	26,5 1.04
24-24	1 1/2-11	-24	87,0 3.43	50,0 1.97	32,5 1.28
32-32	2-11	-32	101,0 3.98	54,0 2.13	44,5 1.75

\*Ø dimension is tube O.D. and refers to mating component when not called out on the illustration.

NOTE: For correct socket part number, see page 65.

# Reusable Fittings


## 100R5 Style

### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### Metric Male 60° DIN 7631/7647


**07.024-**



Dash Size	Thread	Hose Size	A	D	EØ
			mm in	mm in	mm in
07.024-					
4-4	M12 x 1.5	-04	45,0 1.77	26,0 1.02	3,2 .13
6-5	M14 x 1.5	-05	47,5 1.87	27,5 1.08	4,5 .18
8-6	M16 x 1.5	-06	50,0 1.97	27,0 1.06	6,0 .24
10-8	M18 x 1.5	-08	59,0 2.32	30,0 1.18	9,0 .35
13-10	M22 x 1.5	-10	65,0 2.56	32,0 1.26	11,5 .45
16-12	M26 x 1.5	-12	72,5 2.85	32,5 1.28	14,0 .55
20-16	M30 x 1.5	-16	63,0 2.48	31,0 1.22	21,0 .83
25-20	M38 x 1.5	-20	67,5 2.66	33,0 1.30	26,5 1.04
32-24	M45 x 1.5	-24	70,0 2.76	33,0 1.30	32,5 1.28
40-32	M52 x 1.5	-32	84,0 3.31	37,0 1.46	44,5 1.28
50-32	M65 x 2	-32	87,0 3.42	40,0 1.57	44,5 1.75
60-40	M78 x 2	-40	94,5 3.72	46,0 1.81	56,0 2.20
70-48	M90 x 2	-48	100,5 3.96	52,0 2.05	71,0 2.80

### Metric Male 24° DIN 3901/3902 I.Rh.


**07.003-**



Dash Size	Thread	Hose Size	A	D	EØ	RØ
			mm in	mm in	mm in	mm in
07.003-						
6-4	M12 x 1.5	-04	45,0 1.77	26,0 1.02	3,2 .13	6,0 .24
8-5	M14 x 1.5	-05	47,5 1.87	27,5 1.08	4,5 .18	8,0 .31
10-6	M16 x 1.5	-06	51,0 2.01	28,0 1.10	6,0 .24	10,0 .39
12-6	M18 x 1.5	-06	51,0 2.01	28,0 1.10	6,0 .24	12,0 .47
12-8	M18 x 1.5	-08	60,0 2.36	30,5 1.20	9,0 .35	12,0 .47
15-10	M22 x 1.5	-10	65,0 2.56	32,0 1.26	11,5 .45	15,0 .59
18-10	M26 x 1.5	-10	65,0 2.56	32,0 1.26	11,5 .45	18,0 .71
18-12	M26 x 1.5	-12	72,5 2.85	32,5 1.28	14,0 .55	18,0 .71
22-16	M30 x 2	-16	65,0 2.56	32,5 1.28	21,0 .83	22,0 .87
28-20	M36 x 2	-20	67,5 2.66	33,0 1.30	26,5 1.04	28,0 1.10
35-24	M45 x 2	-24	72,0 2.83	35,0 1.38	32,5 1.28	35,0 1.38
42-32	M52 x 2	-32	86,0 3.38	39,0 1.54	44,5 1.75	42,0 1.65

### Metric Male 24° DIN 3901/3902 s.Rh.

**07.026-**



Dash Size	Thread	Hose Size	A	D	EØ	RØ
			mm in	mm in	mm in	mm in
07.026-						
8-4	M16 x 1.5	-04	47,0 1.85	28,0 1.10	3,2 .13	8,0 .31
10-5	M18 x 1.5	-05	49,5 1.95	29,5 1.16	4,5 .18	10,0 .39
12-6	M20 x 1.5	-06	52,0 2.05	29,0 1.14	6,0 .24	12,0 .47
14-8	M22 x 1.5	-08	63,0 2.48	33,5 1.32	9,0 .35	14,0 .55
16-10	M24 x 1.5	-10	67,0 2.64	34,0 1.34	11,5 .45	16,0 .63
20-12	M30 x 2	-12	78,5 3.09	38,5 1.52	14,0 .55	20,0 .79
25-16	M36 x 2	-16	69,0 2.72	36,5 1.44	21,0 .83	25,0 .98
30-20	M42 x 2	-20	73,5 2.89	39,0 1.54	26,5 1.04	30,0 1.18
38-24	M52 x 2	-24	80,0 3.15	43,0 1.69	32,5 1.28	38,0 1.50

\*RØ dimension is tube O.D. and refers to mating component when not called out on the illustration.

NOTE: For correct socket part number, see page 65.

# Reusable Fittings

## 100R5 Style


### For use with Hose:

302A, 303, 1503, 2580, 2651,  
FC234, FC300, FC321, FC350,  
FC355

### Metric Female Swivel

### 60° DIN 7631/7647


**07.036-**



Dash Size	Thread	Hose Size	A	D	EØ
			mm in	mm in	mm in
<b>07.036-</b>					
20-16	M30 x 1.5	-16	72,5 2.85	40,9 1.61	21,0 .83
25-20	M38 x 1.5	-20	76,5 3.01	42,0 1.65	26,5 1.04
32-24	M45 x 1.5	-24	82,0 3.23	45,0 1.77	32,5 1.28
40-32	M52 x 1.5	-32	93,5 3.68	46,5 1.83	44,5 1.75
50-32	M65 x 2	-32	93,5 3.68	46,5 1.83	44,5 1.75
60-40	M78 x 2	-40	103,0 4.06	54,5 2.15	56,0 2.20
70-48	M90 x 2	-48	108,5 4.27	60,0 2.36	71,0 2.80

### Metric Universal Female Swivel 24° DIN 3901/3902 I.Rh.


**07.002-**



Dash Size	Thread	Hose Size	A	D	EØ	RØ
			mm in	mm in	mm in	mm in
<b>07.002-</b>						
4-4†	M12 x 1.5	-04	51,0 2.01	32,0 1.26	3,2 .13	6,0 .24
6-5†	M14 x 1.5	-05	53,5 2.11	33,5 1.32	4,5 .18	8,0 .31
8-6†	M16 x 1.5	-06	56,5 2.22	33,5 1.32	6,0 .24	10,0 .39
10-8†	M18 x 1.5	-08	67,0 2.64	37,5 1.48	9,0 .35	12,0 .47
13-10†	M22 x 1.5	-10	73,0 2.87	40,5 1.59	11,5 .45	15,0 .59
16-12†	M26 x 1.5	-12	83,5 3.29	43,5 1.71	14,0 .55	18,0 .71
22-16	M30 x x 2	-16	74,0 2.91	41,5 1.63	21,0 .83	22,0 .87
28-20	M36 x x 2	-20	78,0 3.07	43,5 1.71	26,5 1.04	28,0 1.10
35-24	M45 x x 2	-24	81,5 3.21	44,5 1.75	32,5 1.28	35,0 1.38
42-32	M52 x x 2	-32	94,0 3.70	47,0 1.85	44,5 1.75	42,0 1.65

### Metric Universal Female Swivel 24° DIN 3901/3902 s.Rh.


**07.155-**



Dash Size	Thread	Hose Size	A	D	EØ	RØ
			mm in	mm in	mm in	mm in
<b>07.155-</b>						
8-4	M16 x 1.5	-04	52,5 2.07	33,5 1.32	3,2 .13	08,0 .31
10-5	M18 x 1.5	-05	55,0 2.17	35,0 1.38	4,5 .18	10,0 .39
12-6	M20 x 1.5	-06	59,5 2.34	36,5 1.44	6,0 .24	12,0 .47
14-8	M22 x 1.5	-08	68,5 2.70	39,0 1.54	9,0 .35	14,0 .55
16-10	M24 x 1.5	-10	74,5 2.93	41,5 1.63	11,5 .45	16,0 .63
20-12	M30 x 2	-12	85,5 3.37	45,5 1.79	14,0 .55	20,0 .79
25-16	M36 x 2	-16	75,0 2.95	42,5 1.67	21,0 .83	25,0 .98
30-20	M42 x 2	-20	78,5 3.09	44,0 1.73	26,5 1.04	30,0 1.18
38-24	M52 x 2	-24	84,0 3.31	47,0 1.85	32,5 1.28	38,0 1.50

### Komatsu 30° Metric Female Swivel

**FC5954-**



Dash Size	Thread	Hose Size	A	D	EØ
			mm in	mm in	mm in
<b>FC5954-</b>					
0306S	M18 x 1.5	-06	63,3 2.49	40,4 1.59	6,1 .24
0410S	M22 x 1.5	-10	78,7 3.10	46,2 1.82	9,4 .37
0512S	M24 x 1.5	-12	90,2 3.55	50,3 1.98	12,2 .48
0612S	M30 x 1.5	-12	95,5 3.76	55,6 2.19	14,0 .55
1016S	M33 x 1.5	-16	90,2 3.55	57,9 2.28	20,8 .82
1424S	M42 x 1.5	-24	107,7 4.12	67,8 2.67	30,2 1.19

\*RØ dimension is tube O.D. and refers to mating component when not called out on the illustration.

NOTE: For correct socket part number, see page 65.

† Universal fitting also mates with DIN 7631/7647 60° connections.