

1830

Graphite PTFE Braided Packing

Meets Strict Specifications for Rotating Equipment

Chesterton 1830 is an advanced combination of graphite and expanded PTFE in a single filament yarn packing designed to rigid specifications. It is well-suited for use in pumps, valves, agitators, mixers, and other rotating equipment. The PTFE resin is combined with graphite and lubricants using the latest technologies, resulting in a high-quality yarn filament. Due to the unique characteristics of this packing it is gentle on the shaft/sleeves, while still being pliable and conforming to adjust to shaft/sleeve and stuffing box irregularities.

Technical Data

Pressure Limit	22 bar g (320 psig)
Shaft Speed	18 m/s (3600 fpm)
Temperature Limit	260°C (500°F)
Chemical Resistance	pH 0 – 14 with the exception of strong oxidizers in the 0 – 2 pH range



- Excellent chemical resistance
- High linear strength
- UV resistance
- Low friction, less heat generation, and non-abrasiveness extends shaft and shaft sleeve life
- Easy installation and removal
- Low leakage and long life



Applications

For use in a pumps, valves, agitators, mixers and other rotating equipment in a wide range of applications and industries.

Size		Packaged ± 10%		Item Number
mm	Inch	kg	lbs	
4.7	3/16	0.908	2	175910
6.4	1/4	0.908	2	175911
		2.270	5	175912
8.0	5/16	0.908	2	175913
		2.270	5	175914
9.5	3/8	0.908	2	175915
		2.270	5	175916
		4.540	10	175917
10.0	-	0.908	2	175918
		2.270	5	175919
11.0	7/16	0.908	2	175920
		2.270	5	175921
12.0	-	0.908	2	175922
		2.270	5	175923
12.7	1/2	0.908	2	175924
		2.270	5	175925
		4.540	10	175926
14.0	9/16	2.270	5	175927
		4.540	10	175928
16.0	5/8	4.540	10	175929
17.5	11/16	4.540	10	175930
19.0	3/4	4.540	10	175931
20.0	-	4.540	10	175932
20.5	13/16	These sizes are available upon request.		
22.0	7/8	4.540	10	175933
24.0	15/16	4.540	10	175934
25.4	1	4.540	10	175935

Chesterton ISO certificates available on chesterton.com/corporate/iso

Distributed by:

Technical data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. Chesterton Company disclaims all warranties express or implied, including warranties of merchantability and fitness for a particular purpose. Liability, if any, is limited to product replacement only. Any images contained herein are for general illustrative or aesthetic purposes only and are not intended to convey any instructional, safety, handling or usage information or advice respecting any product or equipment. Please refer to relevant Safety Data Sheets, Product Data Sheets, and/or Product Labels for safe use, storage, handling, and disposal of products, or consult with your local Chesterton sales representative.

© 2021 A.W. Chesterton Company.

® Registered trademark owned by A.W. Chesterton Company in USA and other countries, unless otherwise noted.



A.W. Chesterton Company
860 Salem Street
Groveland, MA 01834 USA

Telephone: 781-438-7000
Fax: 978-469-6528
chesterton.com

Form No. 088124
1830 PDS – English
03/21