



Gates Clean Master Pressure Wash 3000



Inside Diameter	Outside Diameter	Max. W.P. (psi)	Vac. (In. Hg)	MBR (in)	Wt. Per Ft.	Length	Stock OR MTO	Gates Item #	Color
.375"	9.5mm	3000	30.0	2.5	.23	300	MTO	4657-2402	Black
.375"	9.5mm	3000	30.0	2.5	.23	1000	MTO	4657-2401	Black
.375"	9.5mm	3000	30.0	2.5	.23	300	MTO	4657-2404	Blue
.375"	9.5mm	3000	30.0	2.5	.23	1000	Stock	4657-2403	Blue
.375"	9.5mm	3000	30.0	2.5	.23	300	MTO	4657-2416	Gray
.375"	9.5mm	3000	30.0	2.5	.23	300	MTO	4657-2417	Yellow
.375"	9.5mm	3000	30.0	2.5	.24	1000	MTO	4657-2652	Yellow

RECOMMENDED FOR: Hot and cold water high-pressure cleaning equipment where heavy-duty service is required. Specially compounded cover to handle pressure washer environment.

CAUTION: Not recommended for steam service. Use bend restrictors to extend service life.

TEMPERATURE: -40°F to +250°F (-40°C to +121°C) Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life.

CONSTRUCTION:
Tube: Type C (Nitrile). Black
Reinforcement: Braided, high tensile steel wire.
Cover: Type C2 (Modified Nitrile). Non-marking except for black

COUPLINGS: 74 Gates MegaCrimp couplings

STANDARDS: Exceeds EN1829-2.