



HANNA RUBBER COMPANY

Specification Sheet



PVC Tubing

Physical Properties

- **Color:** Clear
- **Hardness, Shore A ± 5 :** 68
- **Tensile Strength, psi:** 1900
- **Elongation at Break, %:** 400
- **Brittle Temperature:** 41°F
- **Max. Operating Temperature:** 175°F
- **Max. Operating Temperature for NSF:** 120°F

Product Number	ID (in.)	OD (in.)	Wall (in.)	Available Lengths	Working PSI (at 70°F)	Burst PSI (at 70°F)	Weight (lbs/100 ft)
16-PVC-.06X.03	.063 (1/16)	.125 (1/8)	.031 (1/32)	500	33	132	0.51
16-PVC-.09X.03	.094 (3/32)	.156 (5/32)	.031 (1/32)	500	42	168	0.68
16-PVC-.12X.03	.125 (1/8)	.188 (3/16)	.031 (1/32)	500	44	176	0.85
16-PVC-.12X.06	.125 (1/8)	.250 (1/4)	.063 (1/16)	100, 500	68	272	2.1
16-PVC-.18X.03	.188 (3/16)	.250 (1/4)	.031 (1/32)	100	33	132	1.2
16-PVC-.18X.06	.188 (3/16)	.313 (5/16)	.063 (1/16)	100, 500	55	220	2.7
16-PVC-.18X.09	.188 (3/16)	.375 (3/8)	.094 (3/32)	100	70	280	4.6
16-PVC-.25X.06	.250 (1/4)	.375 (3/8)	.063 (1/16)	50, 100, 500	55	220	3.4
16-PVC-.25X.09	.250 (1/4)	.438 (7/16)	.094 (3/32)	100	60	240	5.7
16-PVC-.25X.12	.250 (1/4)	.500 (1/2)	.125 (1/8)	100	70	280	8.3
16-PVC-.31X.06	.313 (5/16)	.438 (7/16)	.063 (1/16)	100, 500	50	200	4.2
16-PVC-.31X.09	.313 (5/16)	.500 (1/2)	.094 (3/32)	100	60	240	6.8
16-PVC-.31X.12	.313 (5/16)	.563 (9/16)	.125 (1/8)	100	70	280	9.7
16-PVC-.37X.06	.375 (3/8)	.500 (1/2)	.063 (1/16)	100, 500	40	160	4.8
16-PVC-.37X.09	.375 (3/8)	.563 (9/16)	.094 (3/32)	100	50	200	7.8
16-PVC-.37X.12	.375 (3/8)	.625 (5/8)	.125 (1/8)	100	65	260	11.1
16-PVC-.37X.18	.375 (3/8)	.750 (3/4)	.188 (3/16)	100	66	264	18.7
16-PVC-.43X.12	.438 (7/16)	.688 (11/16)	.125 (1/8)	100	50	200	12.5
16-PVC-.5X.06	.500 (1/2)	.625 (5/8)	.063 (1/16)	100, 500	30	120	6.2
16-PVC-.5X.09	.500 (1/2)	.688 (11/16)	.094 (3/32)	100	40	160	9.9
16-PVC-.5X.12	.500 (1/2)	.750 (3/4)	.125 (1/8)	50, 100	45	180	13.9
16-PVC-.56X.09	.563 (9/16)	.750 (3/4)	.094 (3/32)	100	40	160	11
16-PVC-.62X.06	.625 (5/8)	.750 (3/4)	.063 (1/16)	100	20	80	7.6
16-PVC-.62X.09	.625 (5/8)	.813 (13/16)	.094 (3/32)	100	35	140	12
16-PVC-.62X.12	.625 (5/8)	.875 (7/8)	.125 (1/8)	50, 100	40	160	16.6

Product Number	ID (in.)	OD (in.)	Wall (in.)	Available Lengths	Working PSI (at 70°F)	Burst PSI (at 70°F)	Weight (lbs/100 ft)
16-PVC-.62X.15	.625 (5/8)	.938 (15/16)	.156 (5/32)	100	50	200	21.7
16-PVC-.75X.06	.750 (3/4)	.875 (7/8)	.063 (1/16)	100	19	76	9
16-PVC-.75X.12	.750 (3/4)	1.000	.125 (1/8)	50, 100	35	140	19.4
16-PVC-.75X.15	.750 (3/4)	1.063 (1-1/16)	.156 (5/32)	100	40	160	25.1
16-PVC-.75X.18	.750 (3/4)	1.125 (1-1/8)	.188 (3/16)	100	44	176	31.2
16-PVC-.75X.25	.750 (3/4)	1.250 (1-1/4)	.250 (1/4)	100	44	176	44.3
16-PVC-.87X.12	.875 (7/8)	1.125 (1-1/8)	.125 (1/8)	100	30	120	22.1
16-PVC-1X.12	1.000	1.250 (1-1/4)	.125 (1/8)	50, 100	28	112	25
16-PVC-1X.18	1.000	1.375 (1-3/8)	.188 (3/16)	100	45	180	39.4
16-PVC-1X.25	1.000	1.500 (1-1/2)	.250 (1/4)	100	50	200	55
16-PVC-1.25X.12	1.250 (1-1/4)	1.500 (1-1/2)	.125 (1/8)	100	22	88	30.5
16-PVC-1.25X.18	1.250 (1-1/4)	1.625 (1-5/8)	.188 (3/16)	50, 100	31	124	47.8
16-PVC-1.25X.25	1.250 (1-1/4)	1.750 (1-3/4)	.250 (1/4)	50	45	180	66.5
16-PVC-1.5X.12	1.500 (1-1/2)	1.750 (1-3/4)	.125 (1/8)	50, 100	19	76	36
16-PVC-1.5X.18	1.500 (1-1/2)	1.875 (1-7/8)	.188 (3/16)	50, 100	26	104	56.1
16-PVC-1.5X.25	1.500 (1-1/2)	2.000	.250 (1/4)	50	40	160	77.5
16-PVC-1.75X.12	1.750 (1-3/4)	2.000	.125 (1/8)	50	16	64	41.5
16-PVC-1.75X.25	1.750 (1-3/4)	2.250 (2-1/4)	.250 (1/4)	50	29	116	80
16-PVC-2X.12	2.000	2.250 (2-1/4)	.125 (1/8)	50	14	56	47.1
16-PVC-2X.25	2.000	2.500 (2-1/2)	.250 (1/4)	50	35	140	99.7
16-PVC-2.25X.25	2.250 (2-1/4)	2.750 (2-3/4)	.250 (1/4)	50	24	96	111
16-PVC-2.5X.25	2.500 (2-1/2)	3.000	.250 (1/4)	50	22	88	122
16-PVC-3X.25	3.000	3.500 (3-1/2)	.250 (1/4)	50	19	76	144
16-PVC-4X.37	4.000	4.750 (4-3/4)	.375 (3/8)	50	21	84	300

Hanna Rubber accepts no responsibility for results obtained. Each user of these products, or information, should perform their own tests to determine the suitability of the material. Hanna Rubber does not guarantee that the user will obtain the same results. The data and information are subject to change without notice.