

Description:

V4986-R-27730

Date Issued

Page 1 of 7 05/20/2022

SECTION 1: IDENTIFICATION

Manufacturer Hanna Rubber Company

Address 908 West 25th Street

Kansas City, MO

Information Telephone

Number

816-221-9600

Emergency Contact

Number: **Recommended Use**

800-424-9300 (CHEMTREC)

Adhesive

SECTION 2: HAZARD(S) IDENTIFICATION

Classifications Skin Irritation: Category 2

Eye Damage: Category 2A Reproductive Toxicity: Category 2

STOT Single Exposure: Category 3 STOT Repeated Exposure: Category 2 Aspiration: Category 1

Flammable Liquid: Category 2 Aquatic Hazard Acute: Čategory 1 Aquatic Hazard Long-term: Čategory 1

Pictograms





GHS Signal Word DANGER!

Hazard Statements Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Highly flammable liquid and vapor.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

Precautionary Statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking. Keep cool.

Ground and bond container and receiving equipment.



Description:

V4986-R-27730

Date Issued

Page 2 of 7 05/20/2022

IF ON SKIN: Take off all contaminated clothing and rinse skin with water.

Avoid release to the environment. Collect spillage. Avoid breathing vapors. Use in a well-ventilated area.

IF INHALED: Call a doctor if you feel unwell. Remove person to fresh air and keep

comfortable for breathing

Do not breathe vapors. Get medical attention if you feel unwell.

IF SWALLOWED: Call a doctor if you feel unwell. Do NOT induce vomiting.

IF ON SKIN: Take off contaminated clothing and wash before reuse. Wash skin with

plenty of water. If skin irritation occurs: Get medical attention.

Potential Health Effects

Principal Routes of Exposure Inhalation, skin absorption, eye contact

Acute Effects

Eye: Contact with eyes may cause irritation. Direct contact with liquid or vapors may

cause stinging, tearing, redness, swelling and eye damage.

Skin: May cause skin irritation and/or dermatitis. Prolonged or repeated contact or

exposure to vapors may cause redness, burning, and drying and cracking of skin.

Inhalation: Breathing high concentrations of vapors may cause irritation of the nose and throat

Breathing high concentrations of vapors may cause irritation of the nose and throat or signs of nervous system depression (e.g., headache, nausea, drowsiness,

dizziness, vomiting, loss of coordination and fatigue)

Ingestion: Ingestion may cause irritation of the digestive tract, nausea, vomiting, and signs of

nervous system depression

Chronic Effects Avoid repeated exposure. May cause blood damage. Repeated contact may cause

allergic reactions in very susceptible persons.

Aggravated Medical Conditions Pre-existing eye, skin or respiratory disorders may be aggravated by exposure to this

product.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Designation	CAS No.	% by Weight
Heptane	142-82-5	22 - 40%
Acetone	67-64-1	22 - 40%
Toluene	108-88-3	22 - 40%

Any remaining ingredients (to comprise 100% of the product) should be considered a proprietary blend of non-hazardous substances, or materials below threshold reporting limits.

SECTION 4: FIRST AID MEASURES

General Advice Show this safety data sheet to the doctor in attendance

Eyes Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for

thorough irrigation. If irritation persists, get immediate medical attention.

Skin Wash affected area thoroughly with soap and water. Remove contaminated clothing

and wash affected areas thoroughly with mild soap. If skin irritation persists, get

immediate medical attention.

Inhalation Move to fresh air. If not breathing, give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult, give oxygen and get immediate medical

attention. (V4986-R-27780)



Description:

V4986-R-27730

Date Issued

Page 3 of 7 05/20/2022

IngestionDo not induce vomiting seek immediate medical attention. If vomiting occurs, keep

head lower than hips to prevent aspiration.

Notes to Physician Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media Carbon dioxide, dry chemicals, foam. Water may be helpful in keeping adjacent

containers cool; avoid spreading the liquid with water used for cooling. Water-based

sprinkler systems may help contain larger fires.

Special Protective Equipment and firefighting procedures

Wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved

or equivalent) and full protective gear.

Specific hazards arising from the

chemical

Closed containers may rupture if exposed to fire or extreme heat. May produce toxic fumes if burning

fumes if burning.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal PrecautionsUse personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be

advised if significant spillages cannot be contained.

Methods for Clean-up Dam up. Soal

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly

labeled containers. Clean contaminated surface thoroughly.

Other Information None known.

SECTION 7: HANDLING & STORAGE

HandlingUse only in area provided with appropriate exhaust ventilation. Do not breathe vapors

or spray mist. Wear appropriate personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open

flames, hot surfaces and sources of ignition.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away

from extremes of heat or cold. Keep in properly labeled containers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Note: Any items listed in the above with workplace control parameters which are not listed in section 3 are below threshold reporting values.

REL - Recommended Exposure Limits

TLV - Threshold Limit Value

Exposure Limits

Components with workplace control parameters:

Hazardous Components OSHA PEL ACGIH TLV

Heptane 500 400



Description:

V4986-R-27730

Date Issued

8.61

Page 4 of 7 05/20/2022

Acetone	1000	250
Toluene	200	20

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Appearance

Eyes/Face Safety goggles or glasses, or full face shield.

Skin Protective gloves and impervious clothing. Consult the glove/clothing manufacturer

for proper selection of materials.

Respiratory In operations where exposure limits are exceeded, use a NIOSH-approved respirator

that has been selected by a technically qualified person for the specific work

conditions.

Hygiene Practices Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing

before re-use. Wash thoroughly after handling. When using, do not eat, drink or

Upper Flammability/Explosive Limit

smoke.

Yellow liquid.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

• •	•	• • •	
Oxidizing Properties	No Data Available	Lower Flammability/Explosive Limit	1.50
Odor	Solvent odor.	Vapor Pressure mm Hg	Not available
Odor Threshold	No Data Available	Vapor Density	Heavier than air
pH Value	No Data Available	Bulk Density (lb/gal)	6.92
Melting Point / Freezing Point	No Data Available	VOC Content (g/L)	461
Boiling Point	133.0 °F [56.1 °C]	VOC Less Water & Exempts (g/L)	612
Flash Point	-4.0 °F [-20.0 °C]	Specific Gravity (g/l)	0.831
Explosive Properties	No Data Available	Auto-Ignition Temperature	No Data Available
Evaporation Rate	Faster than nBuAc	Decomposition Temperature	No Data Available
Flammability (solids)	No Data Available	Partition Coefficient	No Data Available
Solubility in Water	Insoluble	Viscosity	No Data Available

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions. Hazardous polymerization does not occur.

Possibility of Hazardous Reactions None under normal conditions of use.

Conditions to Avoid Keep away from open flames, hot surfaces, static electricity and sources of ignition.



Description:

V4986-R-27730

Date Issued

Page 5 of 7 05/20/2022

Avoid extremes of heat or cold.

Incompatible with strong acids and bases, alkali metals, halogens, and strong Materials to Avoid

oxidizing agents.

Hazardous Decomposition Thermal decomposition can lead to release of irritating gases and vapors. Carbon

monoxide, carbon dioxide, smoke, and other unidentified organic compounds may be

Category 1

formed during combustion.

SECTION 11: TOXICOLOGICAL INFORMATION

Numerical Measures of Toxicity for Individual Components

Likely Routes of Exposure

Inhalation, skin absorption, eye contact.

Category 2

Acute Toxicity Oral: No data; Skin: No data; Inhalation: No Respiratory: No data; Skin: No data Sensitization

Skin: Category 2 No data Irritation Mutagenicity

Reproductive **Toxicity**

Aquatic Toxicity

Persistence and Degradability

Specific Target Organ Toxicity - Single Exposure Category 3

Specific Target Organ Toxicity - Repeated Exposure Category 2

Chronic Toxicity / Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen. If no ingredients are listed below, then there are no known classifications.

Aspiration

Hazards

Component **IARC** NTP **OSHA**

SECTION 12: ECOLOGICAL INFORMATION

The information and data for components are listed individually for areas of ecological consideration below.

No Data Available

Acute and prolonged toxicity to fish: Acute toxicity to aquatic invertebrates: No Data Available Environmental fate and pathways: No Data Available

No Data Available

No Data Available

Mobility in Soil

Bioaccumulative Potential No Data Available **Other Adverse Effects** No Data Available

SECTION 13: DISPOSAL CONSIDERATION

Dispose of in accordance with all applicable local, state, and federal regulations. Do not Waste Disposal Method discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans,



Description:

V4986-R-27730

Date Issued

Page 6 of 7 05/20/2022

or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

SECTION 14: TRANSPORT INFORMATION

The shipping classification in this section is meant as a guide to overall classification of the product. However, transportation classifications may be subject to change with changes in package size. Consult shipper requirements under 49 CFR, IATA and IMDG to assure regulatory compliance.

REGULATION DESCRIPTION

DOT

Proper Shipping Name **ADHESIVES Technical Name** Not available

Hazard Class 3

UN Number UN1133

PGII Packing Group

Placards



ICAO / IATA No Data Available IMDG / IMO No Data Available

SECTION 15: REGULATORY INFORMATION

US TSCA Yes All components are listed or exempt.

Canada DSL Yes All components are listed or exempt.

OSHA Regulatory Status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200)

SARA 313 Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal

Regulations, Part 372.



Description:

V4986-R-27730

Date Issued

Page 7 of 7 05/20/2022

Chemical Designation CAS Number Weight %

Toluene 108-88-3 22 - 40%

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

Chemical Designation CAS Number Weight %

Toluene 108-88-3 22 - 40%

State Regulations

California Prop. 65

This product contains one or more chemicals known to the state of California to cause cancer and/or reproductive harm. Unless chemical names are listed below, these chemicals are present only in trace amounts. www.P65Warnings.ca.gov

Chemical Name CAS Number

Toluene 108-88-3

SECTION 16: OTHER INFORMATION

NFPA is a Health, Flammability and Reactivity rating: 230B

4 SEVERE HAZARD, 3 SERIOUS HAZARD, 2 MODERATE HAZARD, 1 SLIGHT HAZARD, 0 MINIMAL HAZARD, * Chronic Hazard

Date Printed 05/20/2022 SDS Review Date 05/20/2022

DISCLAIMER

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy his self that the product is entirely suitable for his purposes.

***** END OF SAFETY DATA SHEET *****