



R-10460 Medium Closed Cell Sponge

Property	Test Method	Result
Polymer		Silicone
Color		Dark Blue
Sheet Size		36" x 36"
ASTM D-1056		Type II Class A, B, C, D
Compression Deflection	ASTM D 1056	10 psi
Tensile Strength	ASTM D 412	75 psi
Elongation (%)	ASTM D 412	125%
Compression Set	ASTM D 1056	5%
Density	ASTM D 3574	29 lbs./ ft.3
Water Absorption	ASTM D 1056	< 5%
Temperature Range		-100°F to +500°F

Hanna Rubber accepts no responsibility for results obtained. Each user of these products, or information, should perform their own tests to determine the suitability of the material. Hanna Rubber does not guarantee that the user will obtain the same results. The data and information are subject to change without notice.

- Meets UL flammability classification with a 94 HBF rating
- UL 157-recognized weather seal gasket
- Capable of meeting AMS 3195 closed-cell specification
- Capable of meeting MIL-R-6130 Type II Grade A, B and C/ASTM D6576 Type 2, Grade A, B and C
- Boeing BMS1-23, BMS1-60 Type 1 Grade B
- DMS1980 Grade 2
- Meets ASTM D1056 Type 2, Class A, B, C and D/MIL-R-46089

Hanna Rubber Company
908 West 25th Street
Kansas City, Mo. 64108
P: 816-221-9600
www.hannarubber.com