



HANNA RUBBER COMPANY

Specification Sheet



Volt

Recommended For: Heavy duty food grade static dissipative Polyurethane material handling hose.

Temperature Range: -40 to 150 F

Tube: Hose tube complies with FDA(05) requirements. Grounding wire embedded in external helix to prevent material contamination

Reinforcement: Rigid helix design protects hose tube from wear; allows hose to slide easily over rough surfaces. Easy to handle.

Cover: Single – Ply Polyurethane Tube – Provides for longer hose life and lower operating costs versus rubber or PVC hoses.

ID	OD	Working Pressure at 68° F	Maximum Bend Radius	Temperature Range	Weight/ Ft.
1.50"	1.87"	40 PSI	2"	-40 to 150 °F	0.31 LBS/FT
2.00"	2.52"	40 PSI	6"	-40 to 150 °F	0.61 LBS/FT
2.50"	2.96"	40 PSI	7"	-40 to 150 °F	0.76LBS/FT
3.00"	3.60"	40 PSI	9"	-40 to 150 °F	0.91 LBS/FT
4.00"	4.69"	35 PSI	12"	-40 to 150 °F	1.70 LBS/FT
5.00"	5.75"	35 PSI	14"	-40 to 150 °F	2.13 LBS/FT
6.00"	6.81"	30 PSI	16"	-40 to 150 °F	2.53 LBS/FT
8.00"	8.76"	30 PSI	18"	-40 to 150 °F	3.30 LBS/FT

Hanna Rubber accepts no responsibility for results obtained. Each user of these products, or information, should perform their own tests to determine the suitability of the material. Hanna Rubber does not guarantee that the user will obtain the same results. The data and information are subject to change without notice.