



Hanna Rubber Company  
 908 West 25th Street  
 Kansas City, Mo 64108  
 www.hannarubber.com  
 816-221-9600

## AASHTO GRADE PLAIN BEARING PADS

Hanna Rubber Company offers high quality  
 P gqr tpgg \*r qn(ej mqr tpgg+cpf pcwtentwddgt  
 \*r qn(kqr tpgg+dgctkpi rcf o cvgtknvq o ggVCCUJ VQ  
 cpf o cp{ qvj gt ur gekhcvkpu0 Rrklp dgctkpi rcfuctg  
 wugf hqt c xctkqv qhr wtr qugu kp vj g dtkf i g cpf  
 eqputwvkkp kpf wutku0 Vj g{ cmqy hqt gzcrukpp cpf  
 eqpvtcevkkp qhr tgecuvcpf uggneqo r qpgpvu0 Vj g  
 co qwpvqho qxgo gpvf gr gpf u qp vj g vj kempguu qh vj g  
 dgctkpi rcf0 Vj g{ ctg cmq wugf vq o kpk k g vj g  
 ghgeu qhxkdtcvkpp qp vj g utwewtg cpf vq f kuuk cvg  
 pqkug0 Y g j cxg o cvgtknvq o ggvj g ur gekhcvkpu qh  
 cm72 ucvgu cpf Ecpfc0

<b>Type:</b>	Y g r tqxf g dqj P cwtenTwddgt cpf P gqr tpgg0
<b>Sizes:</b>	Qwt O cvgtknku cxckrdrg kp vj kempguu cu vj kp cu 3l: ö cpf cu vj kemcu 3: ö0
<b>Shapes:</b>	Qwt ucpcf ctf r tqf wvku r tqxf gf kp 58ö cpf 6: ö y kf vj u0 Y g ecp ewxqo o qrf xktwcm{ cp{ uk g cpf uj cr g0
<b>Hardness:</b>	CCUJ VQ cmqy u hqt j ctf pguu kp vj g tcpi g qh72 vq 92 f wtqo gvt0

**Specifications met:**

CCUJ VQ O 473/28. i tcf g 5 \*P gqr tpgg+  
 CCUJ VQ O 473/28. i tcf g 7 \*P cwtenTwddgt+  
 CTGO C ugevkpp 3: 0  
 Ecmtcpu. ugevkpp 730  
 CUVO F 62360  
 ECP IEUC

### Standard Material Physical Properties

	<u>Neoprene</u>		
	72	82	92
<b>Hardness, Shore A</b>	67/77	77/87	87/97
<b>Tensile, min. psi</b>	4472	4472	4472
<b>Elongation, % min.</b>	622	572	522
<b>Compression Set % max 22 hours @ 212 degrees F</b>	57	57	57

	<u>Natural Rubber</u>		
	72	82	92
<b>Hardness, Shore A</b>	67/77	77/87	87/97
<b>Tensile, min. psi</b>	4252	4250	4252
<b>Elongation, % min.</b>	602	350	502
<b>Temperature Range</b>	-40°F to +200°F		