

WET EXHAUST HOSE

SERIES 200 Certified Wet Exhaust Softwall Hose SAE J2006 R1

Certified wet exhaust, heavy-wall reinforcement with 2, 4, or 6 plies of synthetic cord. Designed for engine water circulation, heat exchanger, heavy-duty discharge lines and straight marine wet exhaust connections. Meets or exceeds USCG, ABYC, and SAE J2006 R1 Standards for wet exhaust service. Recommended for short, straight connections.

Sizes: ½" I.D. – 16" I.D.

Temperature: -20° to 200° F Continuous

Description: Black with Blue Stripe

Tube and Cover: Black Synthetic EPDM Blend Rubber

Reinforcement: Plies of Synthetic Cord

Packaging: 50 Foot Coils up to 3" I.D., 12.5 Foot Lengths



Marine Hose

ITEM #	I.D. (inch)	I.D. (mm)	O.D. (inch)	O.D. (mm)	WP (psi)
110-0120	1/2"	13.0	0.87	22.0	169
110-0580	5/8"	16.0	1.02	26.0	169
110-0340	3/4"	19.0	1.14	29.0	169
110-0780	7/8"	22.0	1.26	32.0	102
110-1000	1"	25.0	1.36	34.5	102
100-1180	1-1/8"	29.0	1.54	39.0	97
110-1140	1-1/4"	32.0	1.69	43.0	97
110-1560	1-5/16"	33.0	1.69	43.0	97
110-1380	1-3/8"	35.0	1.81	46.0	97
200-1120	1-1/2"	38.0	1.93	49.0	68
200-1580	1-5/8"	41.0	2.05	52.0	68
200-1340	1-3/4"	45.0	2.20	56.0	63
200-1780	1-7/8"	48.0	2.32	59.0	58
200-2000	2"	51.0	2.44	62.0	58
200-2140	2-1/4"	57.0	2.68	68.0	58
200-2380	2-3/8"	60.0	2.80	71.0	87
200-2120	2-1/2"	64.0	2.91	74.0	87
200-2580	2-5/8"	67.0	3.03	77.0	87
200-2780	2-7/8"	73.0	3.27	83.0	77
200-3000	3"	76.0	3.46	88.0	77
200-3184	3-1/8"	79.0	3.58	91.0	73
200-3124	3-1/2"	89.0	3.98	101.0	63
200-3344	3-3/4"	95.0	4.17	106.0	63
200-4004	4"	102.0	4.45	113.0	58
200-4184	4-1/8"	105.0	4.57	116.0	58
200-4124	4-1/2"	114.0	4.92	125.0	63
200-5004	5"	127.0	5.55	141.0	77
200-5124	5-1/2"	140.0	6.06	154.0	68
200-6004	6"	152.0	6.69	170.0	58
200-6584	6-5/8"	168.0	7.32	186.0	58
200-8004	8"	203.0	8.74	222.0	48
200-8584	8-5/8"	219.0	9.37	238.0	48