

Hanna Rubber Company

Continuous Molded Orings

Available in NBR 70-90 / HNBR 70-90 / EPDM 70-90 / FKM 70-90



Mechanical performance comparable to traditional O-Ring manufacturing process

MEASUREMENTS IN MILLIMETERS				MEASUREMENTS IN INCHES			
ID	±	CS	±	ID	±	CS	±
800 ~ Unlimited	6.40 ~	3.00	0.09	31.496 ~ Unlimited	0.25 ~	0.118	0.004
		3.53	0.10			0.139	0.004
		4.00	0.10			0.157	0.004
		4.50	0.10			0.177	0.004
		5.00	0.13			0.197	0.005
		5.33	0.13			0.210	0.005
		5.50	0.13			0.217	0.005
		5.70	0.13			0.224	0.005
		6.00	0.13			0.236	0.005
		6.50	0.15			0.256	0.006
		6.99	0.15			0.275	0.006
		7.30	0.15			0.287	0.006
		7.50	0.15			0.295	0.006
		7.70	0.15			0.303	0.006
		8.00	0.15			0.315	0.006
		8.40	0.15			0.331	0.006
		8.50	0.20			0.335	0.008
		9.00	0.20			0.354	0.008
		9.50	0.20			0.374	0.008
		10.00	0.20			0.394	0.008
		11.00	0.22			0.433	0.009
		12.00	0.24			0.472	0.009
		13.00	0.26			0.512	0.010
		14.00	0.28			0.551	0.011
		15.00	0.30			0.591	0.012
		15.88	0.32			0.625	0.013
		16.00	0.32			0.630	0.013
		18.00	0.36			0.709	0.014
19.00	0.38	0.748	0.015				
25.00	0.50	0.984	0.020				
28.00	0.56	1.102	0.022				
ID	±	CS	±	ID	±	CS	±