



HANNA RUBBER COMPANY

# Specification Sheet



## Style 154 PTFE Compression Packing

Style 154 PTFE compression packing is a PTFE packing with PTFE dispersion. A dense firm packing used in valve and slow speed pump applications. Excellent chemical resistance.

**Temperature:** To 500°F (260°C)

**pH:** 0-14

**Speed:** 1000 FPM

**Pressure:** Pumps-To 300 PSI (20 bar)

**Pressure:** Valves-To 2000 PSI (140 bar)

**Construction:** Interlock Braid

**Comparable to:** Chesterton 1725/ 425, Crane 715/ 1055, Garlock 5900/ 5904, Teadit 2006FDA

|                 |      |       |      |       |        |       |      |       |      |      |      |     |
|-----------------|------|-------|------|-------|--------|-------|------|-------|------|------|------|-----|
| <b>in.</b>      | 1/8" | 3/16" | 1/4" | 5/16" | 3/8"   | 7/16" | 1/2" | 9/16" | 5/8" | 3/4" | 7/8" | 1"  |
| <b>ft./lb.</b>  | 72   | 31    | 19.4 | 12.5  | 9      | 7     | 5.1  | 4.1   | 3.3  | 2.3  | 1.7  | 1.2 |
| <b>lbs./box</b> | 1    | 1     | 2    | 2     | 2 or 5 | 5     | 5    | 5     | 5    | 10   | 10   | 10  |

Hanna Rubber accepts no responsibility for results obtained. Each user of these products, or information, should perform their own tests to determine the suitability of the material. Hanna Rubber does not guarantee that the user will obtain the same results. The data and information are subject to change without notice.