



HANNA RUBBER COMPANY

Specification Sheet



Style 90 Carbon Compression Packing

Style 90 carbon compression packing is a carbon yarn packing impregnated with graphite dispersion. For severe services in pump and valve applications, including super-heated steam, acids, alkalis, etc.

Temperature (atmosphere): To 850°F (455°C)

Temperature (steam): To 1200°F (650°C)

pH: 0-14

Speed: 4000 FPM

Comparable to: Chesterton 370/477-1, Crane 1650CF/1627, Garlock 98/88, Teadit 2002

Pressure: Pumps-To 500 PSI (35 bar)

Pressure: Valves-To 2500 PSI (170 bar)

Construction: Interlock Braid

in.	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	7/8"	1"
ft./lb.	160	58	39	21	15.3	11.7	8.8	7.8	6	4.1	3	2.2
lbs./box	1 or 2	1 or 2	1 or 2	2	2 or 5	5	5	5	5	5 or 10	10	10

Hanna Rubber accepts no responsibility for results obtained. Each user of these products, or information, should perform their own tests to determine the suitability of the material. Hanna Rubber does not guarantee that the user will obtain the same results. The data and information are subject to change without notice.