



HANNA RUBBER COMPANY

# Specification Sheet



## Hanna Series 200 Red Multipurpose Air & Water Hose

### Application

An economical air and water hose, the Hanna Series 200 Red Multipurpose Air & Water Hose is recommended for a wide range of industrial, construction and agricultural applications.

### Construction

**Tube:** EPDM synthetic rubber, ARPM Class C (Limited Oil Resistance)

**Cover:** Red EPDM synthetic rubber, ARPM Class C (Limited Oil Resistance)

**Reinforcement:** Spiral synthetic yarn, 2" is braided

### Temperature Range

-40°F to + 210 °F (-40°C to + 99°C)

### Packaging

90% one piece reels up to 1" I.D.

|              |              |                                  |
|--------------|--------------|----------------------------------|
| 3/16" – 5/8" | 750' reels   | Maximum 3 pieces, 50' increments |
| 3/4"         | 600' reels   | Maximum 3 pieces, 50' increments |
| 1"           | 450' reels   | Maximum 3 pieces, 50' increments |
| 1 1/4"       | 400' reels   | Maximum 3 pieces, 50' increments |
| 1 1/2"       | 300' reels   | Maximum 3 pieces, 50' increments |
| 2"           | 200' cartons | Maximum 3 pieces, 50' increments |

### Branding

**Example:** 1/2" Hanna Series 200 Red Multipurpose Air & Water Hose 200 psi WP Made in USA

| Size   | Inside Diameter |      | Outside Diameter |      | Weight<br>lbs./ft | Working Pressure |      |
|--------|-----------------|------|------------------|------|-------------------|------------------|------|
|        | IN              | MM   | IN               | MM   |                   | psi              | Mpa  |
| 1/4"   | 0.25            | 6.4  | .5               | 12.7 | .09               | 200              | 1.38 |
| 3/8"   | 0.38            | 9.6  | .67              | 17.0 | 0.15              | 200              | 1.38 |
| 1/2"   | 0.50            | 12.7 | .81              | 20.6 | 0.20              | 200              | 1.38 |
| 3/4"   | 0.75            | 19.1 | 1.12             | 28.5 | 0.34              | 200              | 1.38 |
| 1"     | 1.00            | 25.4 | 1.44             | 36.8 | 0.54              | 200              | 1.38 |
| 1 1/4" | 1.25            | 31.8 | 1.73             | 44.0 | 0.75              | 200              | 1.38 |
| 1 1/2" | 1.50            | 38.1 | 1.98             | 50.4 | 0.86              | 200              | 1.38 |
| 2"     | 2.00            | 50.8 | 2.50             | 63.5 | 1.16              | 200              | 1.38 |