



HANNA RUBBER COMPANY

# Specification Sheet

## WATER SUCTION AND DISCHARGE



This heavy-duty water suction and discharge hose is designed for use in construction, dewatering, agricultural and industrial applications. Abrasion and ozone resistant EPDM cover for heavy duty industrial applications. EPDM tube designed to handle residual chemicals in water transfer applications.

Comparable Products: Contitech Versiflo® 150 Water S&D, Gates Water Master, Barracuda, Eaton Otter Water

|                           |                                     |
|---------------------------|-------------------------------------|
| TUBE:                     | BLACK EPDM BLEND                    |
| REINFORCEMENT:            | 2 PLY TEXTILE AND WIRE HELIX        |
| COVER:                    | BLACK EPDM BLEND                    |
| TEMPERATURE:              | -13°F to 180°F                      |
| BRANDING:                 | WATER SUCTION AND DISCHARGE 150 PSI |
| PACKAGING SPECIFICATIONS: | 100' COILS AND 20' SECTIONS         |

| SA #         | ID (IN) | OD (IN) | WP (PSI) | BURST (PSI) | BEND RADIUS (IN) | VACUUM RATING (HG) | WEIGHT | PACKAGING |
|--------------|---------|---------|----------|-------------|------------------|--------------------|--------|-----------|
| 1004103-100  | 1.00    | 1.40    | 150      | 450         | 4                | 29                 | 0.52   | 100'      |
| 1004103-125  | 1.25    | 1.69    | 150      | 450         | 5                | 29                 | 0.67   | 100'      |
| 1004103-150  | 1.50    | 2.00    | 150      | 450         | 6                | 29                 | 0.99   | 100'      |
| 1004103-200  | 2.00    | 2.50    | 150      | 450         | 9                | 29                 | 1.29   | 20', 100' |
| 1004103-250  | 2.50    | 2.99    | 150      | 450         | 10               | 29                 | 1.55   | 100'      |
| 1004103-300  | 3.00    | 3.57    | 150      | 450         | 14               | 29                 | 2.17   | 20', 100' |
| 1004103-400  | 4.00    | 4.57    | 150      | 450         | 19               | 29                 | 2.72   | 20', 100' |
| 1004103-500  | 5.00    | 5.59    | 150      | 450         | 29               | 29                 | 4.70   | 100'      |
| 1004103-600  | 6.00    | 6.73    | 150      | 450         | 32               | 29                 | 5.75   | 20', 100' |
| 1004103-800  | 8.00    | 8.78    | 150      | 450         | 44               | 29                 | 8.51   | 20', 100' |
| 1004103-1000 | 10.00   | 10.95   | 150      | 450         | 50               | 29                 | 10.83  | 20'       |
| 1004103-1200 | 12.00   | 12.90   | 150      | 450         | 66               | 29                 | 12.44  | 20'       |