



HANNA RUBBER COMPANY

# Specification Sheet



## Aeration Tubing

A special weighted flexible PVC tubing that is ideal for trouble free delivery of air to pond aeration systems.

### Construction

Special Black weighted PVC compound ensures durability, reliability, and sink-ability while in use.

### Service Temperature Range

25°F (-4°C) to +150°F (+65°C)

### Features

- Remains flexible for use in a wide range of temperatures.
- Greatly reduces installation time, requires no maintenance following instructions.
- Naturally sinks without the use of additional weights or anchors.
- Available in 3/8", 1/2", 5/8, 3/4 and 1" ID sizes to fit most aeration systems.
- Packaged in coils or reels depending on application lengths required.

### Applications

- Pond and lake aeration
- Water recirculation
- Ice clearing
- Wastewater lagoons
- Commercial hatcheries

ID	OD	Roll Length	Approximate Weight
.375"	.690"	300 ft.	60 lbs.
.5"	.960"	200 ft.	80 lbs.
.625"	1.065"	100 ft.	44 lbs.
.75"	1.275"	100 ft.	63 lbs.
1"	1.690"	100 ft.	111 lbs.

Hanna Rubber accepts no responsibility for results obtained. Each user of these products, or information, should perform their own tests to determine the suitability of the material. Hanna Rubber does not guarantee that the user will obtain the same results. The data and information are subject to change without notice.