



HANNA RUBBER COMPANY

Specification Sheet



Braid Reinforced Silicone Tubing

Physical Properties	
Hardness, Shore A ± 5 - Liner	70
Hardness, Shore A ± 5 - Cover	60
Tensile Strength, psi	1000
Elongation at Break, %	350
Brittle Temperature	-80°F
Maximum Operating Temperature	350°F

Product Number	ID (in.)	OD (in.)	Wall (in.)	Available Lengths	Working PSI (at 70°F)	Burst PSI (at 70°F)	Colors	Weight (lbs/100 ft)
6-2900072	.125 (1/8)	.365	.120	100	233	699	Natural	5
16-2900149	.188 (3/16)	.447	.130	100	216	648	Natural	7
16-2900226	.250 (1/4)	.520	.135	100	208	624	Natural	9
16-2900303	.313 (5/16)	.592	.140	100	183	549	Natural	11
16-2900380	.375 (3/8)	.655	.140	100	166	498	Natural	13
16-2900457	.500 (1/2)	.800	.150	100	141	423	Natural	17
16-2900534	.625 (5/8)	.965	.170	50	116	348	Natural	23
16-2900611	.750 (3/4)	1.100	.175	50	91	273	Natural	28
16-2900765	1.000	1.380	.180	50	75	225	Natural	36

Hanna Rubber accepts no responsibility for results obtained. Each user of these products, or information, should perform their own tests to determine the suitability of the material. Hanna Rubber does not guarantee that the user will obtain the same results. The data and information are subject to change without notice.