




HANNA RUBBER COMPANY

Specification Sheet



T600AA Series Hard Wall Marine Exhaust Hose USCG/SAE J1527 A2/B2

General Applications:

Fuel, oil and hydraulic fluids suction and discharge. Suitable for exhaust gas from water cooled stationary or marine diesel engines. Offers maximum flexibility.

Construction:

- **Tube:** Black NBR - exhaust gas, fuel and fire resistant.
- **Reinforcement:** High tensile textile cords with flexible steel helix wire.
- **Cover:** Black NBR/PVC blend - abrasion, ozone, hydrocarbon and fire resistant.

Working Pressure:

Constant Pressure - 2 Bar (30 PSI)

Service Temperature Range:

-4° F (-20°C) to +212° F (+100°C)

Nominal Specifications:

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius at 68 °F (in)	Standard Length (ft)	Weight (lbs/ft)
T600AA062	5/8	16	1.02	26	30	30	2	25/50	0.36
T600AA075	3/4	19	1.14	29	30	30	2 1/4	25/50	0.44
T600AA087	7/8	22	1.26	32	30	30	2 3/4	25/50	0.50
T600AA100	1	25	1.38	35	30	30	3	25/50	0.56
T600AA112	1 1/8	28	1.50	38	30	30	3 1/4	25/50	0.60
T600AA125	1 1/4	32	1.65	42	30	30	3 3/4	25/50	0.65
T600AA137	1 3/8	35	1.77	45	30	30	4 1/4	25/50	0.70
T600AA150	1 1/2	38	1.89	48	30	30	4 1/2	25/50	0.76
T600AA162	1 5/8	42	2.17	52	30	30	5	25/50	0.81
T600AA175	1 3/4	45	2.16	55	30	30	5 1/4	25/50	0.87
T600AA189	1 7/8	48	2.28	58	30	30	5 3/4	25/50	0.91
T600AA200	2	51	2.40	61	30	30	6	25/50	0.99
T600AA225	2 1/4	57	2.64	67	30	30	6 3/4	25/50	1.09
T600AA238	2 3/8	60	2.76	70	30	27	7	25/50	1.25
T600AA250	2 1/2	63	2.87	73	30	27	7 1/2	25/50	1.31
T600AA275	2 3/4	70	3.11	80	30	27	8 1/4	25/50	1.41
T600AA300	3	76	3.39	86	30	27	9	25/50	1.53
T600AA350	3 1/2	90	3.94	100	30	27	10 1/2	25/50	1.91
T600AA400	4	102	4.41	112	30	27	12	25/50	2.12
T600AA450	4 1/2	115	5.00	127	30	27	13 1/2	25/50	2.72
T600AA500	5	127	5.55	141	30	24	15	25/50	3.04

Hanna Rubber accepts no responsibility for results obtained. Each user of these products, or information, should perform their own tests to determine the suitability of the material. Hanna Rubber does not guarantee that the user will obtain the same results. The data and information are subject to change without notice.