



HANNA RUBBER COMPANY

Garlock Competitor Interchange

Garlock Style	Garlock Product Description	Flexitallic	GRI	Klinger	Lamons	Leader	Robco	Teadit	GRAFTECH	SGL
BLUE-GARD® 3000	Aramid Fiber / NBR	SF3500	8500	4401	L-441	1078/940	4401	NA1001		
BLUE-GARD® 3200/3400	Aramid Fiber/ SBR	SF2420	8600	6400	L-640W	960/961	6400	NA1080		
BLUE-GARD® 3300	Aramid Fiber/ Neoprene			5400	L-540	976	5400	NA1076		
BLUE-GARD® 3700	Aramid Fiber/ EPDM			7400		986A	7400			
IFG-5500	Inorganic Fiber/ Nitrile	SF3300	5000	4430	L-443	978	4430			
IFG-5507	Inorganic Fiber/ EPDM									
HTC 9800	Carbon Fiber / SBR	SF5000	8300	4500	L-450					
HTC-9850	Carbon Fiber / NBR					2078	4500	NA1100		
9900	Graphite Fiber / NBR									
THERMa-PUR™	Extreme temperature gasketing	THERMIC-ULITE		MILAM PSS			MILAM PSS			
GYLON® 3500	Silica Filled PTFE	511		2003	L100	2100	ROBCHEM CF-500	1590		
GYLON® 3504	Glass Microsphere Filled Restructured PTFE	500	9000*		L104	2110	ROBCHEM CF-504	1570		
GYLON® 3510	Barium Sulfate Filled Restructured PTFE	533	9200W	2006	L110	2120	ROBCHEM CF-510	1580		
GYLON® 3540	Microcellular Restructured PTFE	600	9600	SOFT CHEM†		2130†	SOFT CHEM†	QUIMFLEX SH†		
GYLON® 3545	Microcellular Restructured PTFE with rigid core	588	9600	SOFT CHEM†		2130†	SOFT CHEM†	QUIMFLEX SH†		
GYLON® 3560	Metal Inserted Restructured PTFE									
GYLON® 3561	Metal Inserted Restructured PTFE									

Garlock Style	Garlock Product Description	Flexitallic	GRI	Klinger	Lamons	Leader	Robco	Teadit	GRAFT-ECH	SGL
FLEXSEAL®	Spiral wound gaskets	Flexitallic	DURLON®	MAXIFLEX			MAXIFLEX	METALFLEX®		
SW	Winding only	R	D	R	W	S	R	911		
RW	Winding and outer ring	CG	DR	CR	WR	SR	CR	913		
RWI	Winding, outer ring and inner ring	CGI	DRI	CRIR	WRI	SRI	CRIR	913M		
Low-Load	Lower seating stress requirements	LS / LSI								
EDGE®	Anti-buckling STABL-LOCK™ inner ring & relief ports									
KAMMPROFILE	Profiled metal gasket	FLEX-PRO™			Kamm-profile	Leader-KAM	MAXIPRO-FILE	Camprofile		
3120	Nuclear grade homogeneous sheet								GTA	N
3122	High purity grade homogeneous sheet								GTA	S
3123	Homogeneous sheet	HS	FGS95		LGL		200-HM		GTB	B
3124	316SS mesh-inserted sheet	WR							GHS	BSC
3125	Laminated sheet	LS		HL			200-HM	2660	GHL	BL
3126	Laminated sheet with 316SS mesh-insert	WR							GHS	BSC
3125SS	Laminated sheet with .002" thick 316SS foil core	SR	FGL316	SLS	LG-SS		204-SFI	2661	GHR	BSSC
3125TC	Laminated sheet with .004" thick tanged metal core	ST	FGL316	PSM*	LG-TC		204-STI	2663	GHE	BTCSS
3125MC	Laminated sheet with .0005" thick MYLAR® core							2664	GHP	BMV
3125NI	Laminated sheet with .005" thick nickel core	NR								
3128	Laminated sheet with multiple .002" thick 316SS foil core (NO ADHESIVE)									HOCH-DRUCK

* - Glass fiber reinforced skived PTFE sheet - low compressibility

† - Competitor products are expanded PTFE, not microcellular PTFE. Expanded PTFE typically has higher creep characteristics