



HANNA RUBBER COMPANY

Specification Sheet

STANDARD HEATER HOSE

Engineered with superior flexibility and durability, Flexfab's standard heater hose is resistant to coolant additives, as well as hardening, cracking, cold leaks, and aging. It's extreme duty cycle tested.

CONSTRUCTION:

- + Silicone hose with 1-ply of nylon fiber reinforcement
 - + Available in:
 - + Stocked in 25' and 50' boxes
 - + Available in longer lengths on standard wooden spools*
- *Continuous lengths are not guaranteed, if continuous lengths are required please contact a sales rep for price and availability

SPECIFICATIONS:

- + Meets or exceeds the operating requirements of SAE J20 R3 Class A ✓
- + Meets or exceeds the operating requirements of TMC RP303B Class I Grade II ✓
- + Standard wall thickness is .140"/.170"
- + Working pressure is 1/3 of the burst pressure
- + Bend radius is 5 times the ID of the hose
- + Resists hardening, cracking, cold leaks, aging, and many chemicals


BENEFITS

- ✓ Box and Spool Lengths Available
- ✓ Extreme Temperature Resistance
- ✓ Superior Flexibility
- ✓ Extreme Duty Cycle Tested for Hostile Engine Environments
- ✓ Durable Construction
- ✓ Resistant to Coolant Additives

CUSTOM ENGINEERED TO WITHSTAND:



TEMPERATURE RANGE:





HANNA RUBBER COMPANY

Specification Sheet

STANDARD HEATER HOSE

| Inside Diameter | | Outside Diameter | | Actual Burst Pressure - PSI | Burst Pressure - PSI | | Weight (LB/FT) | Overall Length (Feet) |
|-----------------|----|------------------|----|-----------------------------|----------------------|-----|----------------|-----------------------|
| Inch | MM | Inch | MM | | SAE J20 R1 | TMC | | |
| 0.25 | 6 | 0.58 | 5 | 320 | 2.0 | 25 | 0 | 25 Box |
| 0.25 | 6 | 0.58 | 5 | 320 | 2.0 | 25 | 0 | 50 Box |
| 0.25 | 6 | 0.58 | 5 | 320 | 2.0 | 25 | 0 | 250 S 00 |
| 0.25 | 6 | 0.58 | 5 | 320 | 2.0 | 25 | 0 | 800 S 00 |
| 0.3 | 8 | 0.64 | 6 | 3.0 | 250 | 25 | 0.28 | 25 Box |
| 0.3 | 8 | 0.64 | 6 | 3.0 | 250 | 25 | 0.28 | 50 Box |
| 0.3 | 8 | 0.64 | 6 | 3.0 | 250 | 25 | 0.28 | 600 S 00 |
| 0.38 | 0 | 0.7 | 8 | 3.0 | 250 | 25 | 0.45 | 25 Box |
| 0.38 | 0 | 0.7 | 8 | 3.0 | 250 | 25 | 0.45 | 50 Box |
| 0.38 | 0 | 0.7 | 8 | 3.0 | 250 | 25 | 0.45 | 250 S 00 |
| 0.38 | 0 | 0.7 | 8 | 3.0 | 250 | 25 | 0.45 | 600 S 00 |
| 0.50 | 3 | 0.83 | 2 | 3.0 | 250 | 25 | 0.8 | 25 Box |
| 0.50 | 3 | 0.83 | 2 | 3.0 | 250 | 25 | 0.8 | 50 Box |
| 0.50 | 3 | 0.83 | 2 | 3.0 | 250 | 25 | 0.8 | 250 S 00 |
| 0.50 | 3 | 0.83 | 2 | 3.0 | 250 | 25 | 0.8 | 00 S 00 |
| 0.63 | 6 | 0.96 | 24 | 300 | 250 | 25 | 0.2.6 | 25 Box |
| 0.63 | 6 | 0.96 | 24 | 300 | 250 | 25 | 0.2.6 | 50 Box |
| 0.63 | 6 | 0.96 | 24 | 300 | 250 | 25 | 0.2.6 | 250 S 00 |
| 0.63 | 6 | 0.96 | 24 | 300 | 250 | 25 | 0.2.6 | 400 S 00 |
| 0.75 | 9 | 0.8 | 27 | 300 | 200 | 25 | 0.25 | 25 Box |
| 0.75 | 9 | 0.8 | 27 | 300 | 200 | 25 | 0.25 | 50 Box |
| 0.75 | 9 | 0.8 | 27 | 300 | 200 | 25 | 0.25 | 250 S 00 |
| 0.75 | 9 | 0.8 | 27 | 300 | 200 | 25 | 0.25 | 300 S 00 |
| 0.88 | 22 | 2 | 3 | 250 | 75 | 25 | 0.287 | 25 Box |
| 0.88 | 22 | 2 | 3 | 250 | 75 | 25 | 0.287 | 50 Box |
| 0.88 | 22 | 2 | 3 | 250 | 75 | 25 | 0.287 | 200 S 00 |
| 00 | 25 | 33 | 34 | 250 | 75 | 25 | 0.324 | 25 Box |
| 00 | 25 | 33 | 34 | 250 | 75 | 25 | 0.324 | 50 Box |
| 00 | 25 | 33 | 34 | 250 | 75 | 25 | 0.324 | 200 S 00 |
| 25 | 32 | 58 | 40 | 200 | 75 | 25 | 0.385 | 25 Box |
| 25 | 32 | 58 | 40 | 200 | 75 | 25 | 0.385 | 50 Box |
| 25 | 32 | 58 | 40 | 200 | 75 | 25 | 0.385 | 50 S 00 |