A SINGER INDUSTRIAL COMPANY

Flexadux® TR HT-W

Engineering & Technical Data

Product Details

- Wearstrip offers additional external abrasion & drag resistance
- Suitable for more demanding positive & negative pressure applications including lawn & leaf collection
- Designed for applications with wide temperature ranges
- Great moisture & UV resistance
- Excellent chemical resistance
- Smooth interior assures minimal friction loss & efficient air flow
- Wall Thickness =.045"

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/ FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/ HG)	WORKING PRESSURE (PSI)
8	1.3	.045	7	3:1	6	7
10	2	.045	9	3:1	6	6
12	2.4	.045	11	3:1	5	5.5

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Heavy weight thermoplastic rubber hose reinforced with a spring steel wire helix & external polypropylene wearstrip
Temperature Range: -60°F to 275°F
Standard Color: Black with Yellow Wearstrip
Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Hanna Rubber Company
908 West 25th Street
Kansas City, MO 64108
816-221-9600
sales@hannarubber.com
www.hannarubber.com